

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



CODE	DESCRIPTION	PRICE/DELIVERY
FC-M-GN3100BT-FC	Freezer Freezer Table 3 Doors, with Monobloc, plug-in system, capacity 417 litres, temperature -18°/-22°C, ventilated, Gastronorm 1/1, ECOLOGICAL in Class E, Gas 290, V.230/1, Kw.0,675, Weight 117 Kg, dim.mm.1795x700x850h	Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION		

FREEZING TABLE - 3 DOOR FREEZER, with MONOBLOC, PLUG-IN SYSTEM, capacity 417 litres, temperature -18°C /-22°C, Gastronorm 1/1 (mm 530x325), ECOLOGICAL in Class E:

- AISI 201 stainless steel structure,
- ventilated refrigeration;
- compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);
- the M line is characterized by: Monobloc refrigeration unit refrigeration group with plug-in system characterized by easy and immediate installation or possible removal/replacement;
- \circ monobloc in highly thermally insulating and completely recyclable plastic material;
- o door with return spring;
- door seal removable without tools:
- o bottom with rounded corners:
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- o circular flow of the cold air so as not to directly touch the product;
- electronic temperature control with digital thermostat;
- o perating temperature -18°/-22°C;
- electric resistance around the door frame to eliminate condensation;
- · automatic defrost with electric resistance and automatic control of the defrost temperature;
- automatic evaporation of condensation water;
- o anti-corrosion treated evaporator;
- o height-adjustable stainless steel feet;
- o possibility of leaning against the wall;
- ECOLOGICAL refrigeration unit with R290 gas;
- insulation thickness 60 mm;
- max ambient temperature/humidity: +35 °C / 55%HR;
- o internal dimensions (mm): 1335 x 530 x 560h;
- external dimensions (mm): 1795 x 700 x 850h.

Supplied:

- o n.3 GN 1/1 grids (mm530x325)
- o n.6 guides.

Options/Accessories :

- $\circ~$ pair of guides for GN 1/1 grill $\,$
- \circ GN 1/1 plasticized grill
- o kit of 4 wheels with a diameter of 120 mm, two of which with brakes

CE mark

Made III ASIA		
TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,675	
net weight (Kg)	117	
gross weight (Kg)	137	
breadth (mm)	1795	
depth (mm)	700	
height (mm)	850	

TECHNICAL CARD

CODE/PICTURES DESCRIPTION PRICE/DELIVERY

FOGRP11



GN 1/1 plasticized gridGastronorm 1/1 plasticized grid

Delivery from 4 to 9 days

Delivery from 4 to 9 days



Pair of guides for GN 1/1 grid support Pair of guides for GN 1/1 grid support



Delivery from 4 to 9 days

Forcar - 4 wheels kit, 2 with brake 4 wheels kit with 120 mm diameter, 2 of which with brake.

