



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
FC-M-GN4100TN-FC	4-door refrigerated table, with monobloc, plug-in system, capacity 553 litres, temperature -2°/+8°C, ventilated refrigeration, Gastronorm 1/1, ECOLOGICAL in Class D, Gas R290, V.230/1, Kw.0,398, Weight 133 Kg, dim.mm.2230x700x850h	Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION		

REFRIGERATED TABLE 4 DOORS, with MONOBLOC, PLUG-IN SYSTEM, temperature -2°C /+8°C, Gastronorm 1/1, Class D:

- **AISI 201 stainless steel structure,**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **circular flow of the cold air so as not to directly touch the product ;**
- **electronic temperature control with digital thermostat ;**
- operating temperature -2°/+8°C;
- electric resistance around the door frame to eliminate condensation;
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- possibility of leaning against the wall;
- **easy interchangeability of doors with two and three drawer chests ;**
- **ECOLOGICAL refrigeration unit with R290 gas;**
- **Energy Class D ;**
- insulation thickness 60 mm;
- max ambient temperature/humidity: +35/80 °C / 55%HR;
- internal dimensions (mm): 1772 x 580 x 588;
- external dimensions (mm): 2230 x 700 x 850

Supplied :

- n.4 GN 1/1 grids (mm 530x325)
- n.8 guides.


Options/Accessories :

- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes
- Set of 2 drawers
- Set of 3 drawers

NOTE: *IT IS RECOMMENDED TO INSTALL ONLY THE CHEST OF DRAWERS WITH 2 DRAWERS IN THE COMPARTMENT NEAR THE REFRIGERATING UNIT, so as not to obstruct the circulation of the cold.*

CE mark
Made in ASIA

TECHNICAL CARD		
power supply		Monofase
Volts		V 230/1
frequency (Hz)		50
motor power capacity (Kw)		0,398
net weight (Kg)		133
gross weight (Kg)		160
breadth (mm)		2230
depth (mm)		700
height (mm)		850
TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY

FOGRP11

GN 1/1 plasticized grid
Gastronorm 1/1 plasticized grid

Delivery from 4 to 9 days

FOCG11

Pair of guides for GN 1/1 grid support
Pair of guides for GN 1/1 grid support

Delivery from 4 to 9 days

FO-RUO120

Forcar - 4 wheels kit, 2 with brake
4 wheels kit with 120 mm diameter, 2 of which with brake.

Delivery from 4 to 9 days

FO-C12-FC

TECHNOCHEF - 2-drawer set, Mod.C12-FC
Set of 2 drawers

Delivery from 4 to 9 days

FO-C13-FC

TECHNOCHEF - 3-drawer set, Mod.C13-FC
Set of 3 drawers

Delivery from 4 to 9 days

