



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-M-GN3200BT-FC</b>	Freezer Freezer Table, 4 Doors and Backsplash, with Monobloc, Plug-in System, capacity 417 litres, temperature -18°/-22°C, Gastronorm 1/1, ventilated, ECOLOGICAL in Class E, Gas R290, V.230 /1, Kw.0,675, Weight 117 Kg, dim.mm.1795x700x950h	<b>Delivery</b> from 8 to 15 days

#### PROFESSIONAL DESCRIPTION

**FREEZING TABLE - FREEZER, Temp.-18°/-22°C, 3 Doors and Backsplash, with Monobloc, Plug-in System, Gastronorm 1/1 (mm 530x325), ECOLOGICAL in Class E:**

- **AISI 201 stainless steel structure,**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **electronic temperature control with digital thermostat ;**
- operating temperature -18°/-22°C;
- electric resistance around the door frame to eliminate condensation;
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- **insulation thickness 60 mm ;**
- **ECOLOGICAL refrigeration unit with R290 gas ;**
- max ambient temperature/humidity: +35 °C / 55%HR;
- internal dimensions (mm): 1335 x 530 x 560h;
- external dimensions (mm): 1795 x 700 x 950h.

**Supplied :**

- n.3 GN 1/1 grids (mm530x325)
- n.3 pairs of guides.

**Options/Accessories :**

- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes


**CE mark**

**Made in ASIA**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,675
<b>net weight (Kg)</b>	117
<b>gross weight (Kg)</b>	137
<b>breadth (mm)</b>	1795
<b>depth (mm)</b>	700
<b>height (mm)</b>	950

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>FOGRP11</b> 	<b>GN 1/1 plasticized grid</b> Gastronorm 1/1 plasticized grid	<b>Delivery</b> from 4 to 9 days

**FOCG11**

**Pair of guides for GN 1/1 grid support**  
Pair of guides for GN 1/1 grid support

**Delivery** from 4 to 9 days

**FO-RUO120**

**Forcar - 4 wheels kit, 2 with brake**  
4 wheels kit with 120 mm diameter, 2 of which with brake.

**Delivery** from 4 to 9 days

