

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



	CODE	DESCRIPTION	PRICE/DELIVERY
	FO-G-GN650TNG	Professional Refrigerator for Beverages, 1 Glass Door, Ventilated, operating temperature -2°/+8°C, capacity 650 litres, Gastro-Norm 2/1, Class B, V.230/1, Kw.0,315, Weight 138 Kg, dim.mm.740x830x2010h	Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION			

REFRIGERATOR for DRINKS-DRINKS, 1 GLASS DOOR, Ventilated, 650 lt, temp.-2°/+8°C, Class B :

- made of AISI 304 stainless steel;
- o external bottom and back panels in galvanized sheet metal;
- bottom with rounded corners;
- suitable for containing Gastro-Norm 2/1 grills or containers (650x530 mm);
- capacity 650 litres;
- ventilated refrigeration;
- o incorporated group;
- evaporator positioned retractably in order to have maximum available space;
- engine compartment with insulated sides;
- electronic temperature control with digital thermostat;
- operating temperature -2°/+8°C;
- automatic defrost with electric resistance and automatic control of the defrost temperature;
- maximum ambient temperature : +32°C;
- maximum ambient humidity: 55% HR;
- refrigerant gas R290;
- energy class B;
- o automatic evaporation of condensation water;
- o anti-corrosion treated evaporator;
- insulation thickness 60 mm;
- o door with return spring and reversible;
- door lock with key;
- door seal removable without tools;
- interior light;
- o feet in AISI 304 stainless steel, adjustable in height.

Supplied:

- o n.3 Gastro-Norm 2/1 grills
- o n.6 guides

Options/Accessories:

- o pair of guides for grid support Code FOCG21
- Gastro-Norm 2/1 plasticized grill Cod.FOGRP21
- $\circ~$ support and guide kit for 600x400 mm trays Code FO-A64
- o kit of 4 wheels diameter 120 mm, 2 of which with brake Code FORUO120

CE mark

Made in ASIA

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,315	
net weight (Kg)	138	
gross weight (Kg)	157	
breadth (mm)	740	
depth (mm)	830	
height (mm)	2010	
TECHNICAL CARD		

CODE/PICTURES DESCRIPTION PRICE/DELIVERY

FOGRP21



Plasticized grid GN 2/1

Plastic grill Gastro-norm 2/1, (cm 53x65)

Delivery from 4 to 9 days

Delivery from 4 to 9 days



Pair of stainless steel guides Pair of stainless steel guides for plasticized grid

FO-RUO120



Delivery from 4 to 9 days

Forcar - 4 wheels kit, 2 with brake 4 wheels kit with 120 mm diameter, 2 of which with brake.

FO-A64

Kit of supports and guides for traysKit of supports and guides for 600x400 mm trays

Delivery from 4 to 9 days

