

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

REFRIGERATED MEAT GRINDER, with 32 MOUTH, with THERMOELECTRIC COOLING SYSTEM, YIELD 500 Kg/h, available in SINGLE-PHASE and THREE-PHASE versions:

- high performance compact refrigerated mincer;
- \circ hermetic reducer in oil bath;
- reducer protected from liquids by a **double insulation system**;
- mouth and driving pin in AISI 304 stainless steel;
- rapid and robust mouth fixing system, patented quick mouth lock;
- removable stainless steel hopper and QUADRO neck for cleaning;
- $\circ~$ square infeed neck for high productivity even in the second pass;
- powerful ventilated motors, for continuous use;
- cooling system with thermoelectric module: WITHOUT COMPRESSOR, without REFRIGERANT Gas, energy saving;
- $\circ \ \ \text{thermoelectric module power: 70 Watt;}$
- $\circ\,$ cooling on the neck and mouth ;
- $\circ \ \ \text{digital control thermometer} \ ;$
- IP 54 commands in 24 Volt with inversion (CE version);
- any maintenance does not require refrigeration;
- $\circ~$ single-phase motor with thermal protection.

Included :

o plate Ø 4.5 mm

Accessories/Options :

- bagger
- giant hopper
- $\circ~$ unger and semi-unger mouth
- medium legs
- hopper cover in plexiglass

CE mark

net weight (Kg)	48
gross weight (Kg)	58
breadth (mm)	355
depth (mm)	500
height (mm)	580

AVAILABLE MODELS

SI-TC32BARCELLONAICE/T



REFRIGERATED MEAT GRINDER, with 32 MOUTH, YIELD 500 Kg/h, V.400/3
REFRIGERATED MEAT GRINDER, with 32 MOUTH, with THERMOELECTRIC COOLING SYSTEM on neck and mouth, YIELD 500 Kg/h, V.400/3, Kw.2,2, Weight 48 Kg, dim.mm.355x500x580h

Delivery

Delivery

SI-TC32BARCELLONAICE/M



REFRIGERATED MEAT GRINDER, with 32 MOUTH, YIELD 500 Kg/h, V.230/1

REFRIGERATED MEAT GRINDER, with 32 SPOUT, with THERMOELECTRIC COOLING SYSTEM on neck and spout, YIELD 500 Kg/h, V.230/1, Kw.1,84, Weight 48 Kg, dim.mm.355x500x580h







Sblocco bocca









Comandi TC ICE TC ICE controls

Griglie di ventilazione TC ICE TC ICE airing take







