

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



operating t	REEZER-FREEZER TABLE, capacity lt.310, temperature -18°/-22°C, ventilated, Gastro- V.230/1, Kw.0,655, Weight 99 Kg, dim. v15x850h	

PROFESSIONAL DESCRIPTION

2 DOOR FREEZER-FREEZER TABLE, capacity 310 I, operating temperature -18°/-22°C :

- internal and external structure in Stainless Steel, with the exception of the external bottom in Galvanized Steel;
- rounded internal corners;
- $\bullet \ \ \text{compartments suitable for inserting Gastro-Norm 1/1 grids or trays} \ (530x325 \ \text{mm}); \\$
- o capacity 310 liters;
- operating temperature -18°/-22°C;
- ${\color{gray} \bullet} \ \, \textbf{CFC-free polyurethane insulation} \ , \ \, \text{injected at high pressure;} \\$
- LV table insulation thickness: 60 mm;
- $\circ~$ doors with automatic closing and magnetic gasket;
- electronic control instrument with 2 NTC probes , evaporator resistance, drain resistance, door edge resistance, thermostatic valve;
- $\circ \ \ \textbf{ventilated refrigeration} \ ;$
- $\circ \ \ removable \ and \ tropicalised \ monobloc \ refrigerating \ unit \ as \ standard \ (ambient \ temperature \ +43°C \ and \ relative \ humidity \ of \ 65\%);$
- working with R404A/R507 gas;
- fully automatic defrosting and evaporation of condensed water;
- equipped with an insulating underlay;
- \circ feet in stainless steel adjustable in height (110/190 H mm);
- o dim.mm.1420x715x850/920.

Included :

o 1 Rilsan grid GN 1/1 and 2 L-shaped stainless steel guides per door

CE mark Made in Italy

TECHNICAL CARD

Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,655
net weight (Kg)	99
breadth (mm)	1420
depth (mm)	715
height (mm)	850