



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TD-TF02MIDBTAL	2 DOOR FREEZER/FREEZER TABLE with UPSTAND, TECNODOM brand, capacity lt.310, operating temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0,655, Weight 100 Kg, dim.mm.1420x715x950h	

PROFESSIONAL DESCRIPTION

2 DOOR FREEZER/FREEZER TABLE with UPSTAND, capacity lt.310, operating temperature -18°/-22°C :

- **internal and external structure in Stainless Steel** , with the exception of the external bottom in Galvanized Steel;
- **rounded internal corners** ;
- **compartments suitable for inserting Gastro-Norm 1/1 grids or trays** (530x325 mm);
- capacity 310 liters;
- operating temperature -18°/-22°C;
- **CFC-free polyurethane insulation** , injected at high pressure;
- **LV table insulation thickness: 60 mm** ;
- doors with automatic closing and magnetic gasket;
- **electronic control instrument with 2 NTC probes** , evaporator resistance, drain resistance, door edge resistance, thermostatic valve;
- **ventilated refrigeration** ;
- removable and tropicalised monobloc refrigerating unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R404A/R507 gas;
- **fully automatic defrosting and evaporation of condensed water**;
- equipped with an insulating underlay;
- **feet in stainless steel adjustable in height** (110/190 H mm);
- dim.mm.1420x715x850/1020.

Included :

- 1 Rilsan grid GN 1/1 and 2 L-shaped stainless steel guides per door

CE mark
Made in Italy

TECHNICAL CARD

power supply | Monofase

Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,655
net weight (Kg)	100
breadth (mm)	1420
depth (mm)	715
height (mm)	950