



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TD-TF04MIDBT</b>	FREEZER/FREEZER TABLE 4 DOORS, TECNODOM brand, capacity lt.630, operating temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0,728, Weight 147 Kg, dim.mm.2320x715x850h	

#### PROFESSIONAL DESCRIPTION

**FREEZER/FREEZER TABLE 4 DOORS, capacity lt.630, operating temperature -18°/-22°C :**

- **internal and external structure in Stainless Steel** , with the exception of the external bottom in Galvanized Steel;
- **rounded internal corners** ;
- **compartments suitable for inserting Gastro-Norm 1/1 grids or trays** (530x325 mm);
- capacity 630 liters;
- operating temperature -18°/-22°C;
- **CFC-free polyurethane insulation** , injected at high pressure;
- **LV table insulation thickness: 60 mm** ;
- doors with automatic closing and magnetic gasket;
- **electronic control instrument with 2 NTC probes** , evaporator resistance, drain resistance, door edge resistance, thermostatic valve;
- **ventilated refrigeration** ;
- removable and tropicalised monobloc refrigerating unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R404A/R507 gas;
- **fully automatic defrosting and evaporation of condensed water**;
- equipped with an insulating underlay;
- **feet in stainless steel adjustable in height** (110/190 H mm);
- dim.mm.2320x715x850/920.

#### Included :

- 1 Rilsan grid GN 1/1 and 2 L-shaped stainless steel guides per door

**CE mark**

**Made in Italy**

#### TECHNICAL CARD

**power supply** | Monofase

<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,728
<b>net weight (Kg)</b>	147
<b>breadth (mm)</b>	2320
<b>depth (mm)</b>	715
<b>height (mm)</b>	850