

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TD-AF07MIDMTN	REFRIGERATOR CABINET 1 door, TECNODOM brand, capacity 700 liters, operating temperature -2 $^{\circ}$ / + 10 $^{\circ}$ C, ventilated refrigeration, Gastro-Norm 2/1, V.230 / 1, Kw.0,385, Weight 110 Kg, dim.mm.710x800x2030h	Delivery from 25 to 35 days

PROFESSIONAL DESCRIPTION

- 1 DOOR FRIDGE CABINET, capacity 700 liters, operating temperature -2 ° / + 10 ° C :
- internal and external structure in stainless steel except bottom, ceiling and external back in galvanized steel;
- o rounded internal corners;
- suitable for containing Gastro-Norm 2/1 grids or trays (650x530 mm);
- o capacity 700 lt;
- \circ operating temperature -2 $^{\circ}$ / + 10 $^{\circ}$ C;
- CFC-free polyurethane insulation, injected at high pressure;
- \circ insulation thickness : 60 mm ;
- self-closing doors with magnetic gasket;
- \circ ventilation stop device when the door is opened;
- front electronic control panel with 2 NTC probes;
- $\circ\;$ resistance to the evaporator;
- $\circ \ \ \textbf{ventilated refrigeration} \ ;$
- extractable and tropicalized monobloc refrigerating unit as standard (ambient temperature + 43 ° C and relative humidity of 65%);
- working with R404A / R507 gas;
- fully automatic defrosting and evaporation of condensation water;
- o reversible door;
- height-adjustable stainless steel feet (110/190 H mm);
- o dim.mm.710x800x2030 / 2100h.

Included:

- o 3 plastic coated Rilsan GN 2/1 grids
- o 6 stainless steel guides
- fan stop

CE mark Made in Italy

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,385	
net weight (Kg)	110	
breadth (mm)	710	
depth (mm)	800	
height (mm)	2030	

