



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



FORCOLD

CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-PZ2610TN-FC	REFRIGERATED PIZZA COUNTER 2 DOORS + DRAWER, granite top with upstand on 3 sides, temperature -2 ° / + 8 ° C, Ventilated, ECOLOGICAL in CLASS C, GAS R600a, V.230 / 1, Kw.0,275, Weight 327 Kg , dim.mm.2020x800x1000h	Delivery from 25 to 35 days

PROFESSIONAL DESCRIPTION

REFRIGERATED PIZZA COUNTER 2 DOORS + DRAWER for bread rolls , operating temperature -2 ° / + 8 ° C, Class C :

- **structure in Aisi 201 stainless steel ,**
- **granite worktop** with backslash on 3 sides,
- **2 refrigerated compartments** able to accommodate **600x400x70h mm loaf boxes ,**
- temperature -2 ° / + 8 ° C;
- **neutral chest of drawers with 7 drawers able to accommodate 7 containers for bread rolls of mm 600x400x70h - NOT INCLUDED**
- **VENTILATED refrigeration ,**
- built-in unit removable for easy maintenance,
- front panel that can be opened with a key,
- **circular flow of cold air** so as not to directly touch the product,
- **electronic temperature control with digital thermostat ,**
- **automatic defrost** with electric resistance,
- **automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- Maximum ambient temperature: + 35 ° C;
- Maximum ambient humidity: 50% HR;
- **ECOLOGICAL refrigerating unit with R600a GAS ;**
- **ENERGY CLASS C;**
- insulation thickness: 60 mm;
- door with return spring;
- door gasket removable without tools;
- bottom with rounded corners;
- **height-adjustable stainless steel feet ;**
- possibility to lean against the wall.



Supplied:

- 7 pairs of guides per door .

NB : Pizza bread holders - NOT INCLUDED.**CE mark****TECHNICAL CARD**

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,275
net weight (Kg)	327
gross weight (Kg)	347
breadth (mm)	2020
depth (mm)	800
height (mm)	1000

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
FO-GRP64 	Forcar - Plasticized Grid 600x400 mm plastic coated grid	Delivery from 4 to 9 days
FO-GUT 	Forcar - Driving Couple Pair of trays for trays	Delivery from 4 to 9 days

FO-GAR



Forcar - Pair of anti-tilt guides
Pair of anti-tilt guides for grill

Delivery from 4 to 9 days

