

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
MZ-690.AP	HOT trolley for temperature maintenance (+30°/+90°C.), with VENTILATED HEATING, 1 Door, for 18 trays measuring 600x400 mm, PITCH between GUIDES 77 mm, V. 230/1, Kw 2.0, Dimensions 670x790x1995h mm	<b>Delivery</b> from 8 to 15 days

## PROFESSIONAL DESCRIPTION

VENTILATED HOT MAINTENANCE trolley, for 18 600x400 mm trays, with a pitch between the guides of 77 mm:

- made entirely of AISI 304-18/10 stainless steel sheet, Scotch-Brite finish;
- **double wall structure**, made with **sandwich panels insulated** with expanded polyurethane and aluminum positioned between the two sheet metal walls;
- $\circ~$  Front swing door that opens to 270 with rubber seal and snap opening handle;
- pair of push handles positioned on both short sides, with PVC handle supports, AISI 304-18/10 stainless steel grip tube, the handles can be used even with the doors open;
- illuminated power switch with mains presence indicator light;
- temperature controlled by a digital thermostat-thermometer from +30° to +90°C., a red light signals the operation of the resistance;
- removable ventilated heating system for easy and convenient cleaning;
- o internal supports with 'L' profiles , depth 30 mm, pitch 77 mm;
- wheels with a diameter of 125 mm, two swivel with brake and two fixed with galvanized steel support;
- perimeter bumper in gray anti-track rubber.
- OPTIONAL ACCESSORIES:
- Door lock;
- Manual humidifier.

## CE mark MADE IN ITALY

TECHNICAL CARD			
power supply	Monofase		
Volts	V 230/1		
frequency (Hz)	50		
motor power capacity (Kw)	2		
breadth (mm)	770		

	depth (mm)	750				
	height (mm)	2000				
TECHNICAL CARD						
CODE/PICTURES		DESCRIPTION	PRICE/DELIVERY			
KR-GR6040AI			Delivery			
	cm, mod. GR6040A	pastry rack, dim.600 x 400 mm, for				