



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	2
net weight (Kg)	135
gross weight (Kg)	145
breadth (mm)	812
depth (mm)	860
height (mm)	1995

PROFESSIONAL DESCRIPTION

HOT MAINTENANCE trolley with VENTILATED heating, for 18 GN 2/1 or 36 GN 1/1 containers, with 77 mm pitch between guides:

- made entirely of **AISI 304-18/10 stainless steel sheet, Scotch-Brite finish** ;
- **double-wall structure** , made with **sandwich panels insulated** with expanded polyurethane and aluminium positioned between the two sheet metal walls;
- **Hinged front door that opens to 270°** with **rubber sealing gasket** and **snap-opening handle**;
- Internal stainless steel tray holder;
- Temperature control via digital thermostat 30°- 90° C;
- **pair of push handles** positioned **on both short sides** , with **PVC** handle supports, **AISI 304-18/10 stainless steel** grip tube, the handles can also be used with the doors open;
- illuminated power switch with **mains presence indicator light** ;
- **temperature controlled** by a **digital thermostat-thermometer** , a red light indicates that the resistance is working;
- **removable fan heating system for easy and convenient cleaning**;
- **internal supports with anti-tipping 'C' profiles, 77 mm pitch** ;
- **wheels with a diameter of 125 mm** , **two swivel** with brake and **two fixed** with galvanized steel support;
- **perimeter bumper** in **grey anti-slip rubber**.

◦ **OPTIONAL - ACCESSORIES:**

- **Door lock;**
- **Manual humidifier.**
- .

CE mark
MADE IN ITALY

CODE	DESCRIPTION	PRICE/DELIVERY
MZ-692.AG	HOT MAINTENANCE trolley with VENTILATED HEATING, 1 Door, Capacity 18 Gastro-Norm 2/1 or 36 Gastro-Norm 1/1 trays, STEP between GUIDES mm 77, V. 230/1, Kw 2.0, dim.mm.812x860x1995h	Delivery from 15 to 25 days