

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
MZ692.AG	HOT MAINTENANCE trolley with VENTILATED HEATING, 1 Door, Capacity 18 Gastro-Norm 2/1 or 36 Gastro-Norm 1/1 containers, PITCH between GUIDES mm 77, V. 230/1, Kw 2.0, dim.mm .812x860x1995h	<b>Delivery</b> from 8 to 15 days

## PROFESSIONAL DESCRIPTION

HOT MAINTENANCE trolley with VENTILATED heating, for 18 GN 2/1 or 36 GN 1/1 containers, with a pitch between the guides of 77 mm:

- made entirely of AISI 304-18/10 stainless steel sheet, Scotch-Brite finish;
- **double wall structure**, made with **sandwich panels insulated** with expanded polyurethane and aluminum positioned between the two sheet metal walls;
- $\circ~$  Front swing door that opens 270° with rubber seal and snap opening handle;
- Internal stainless steel tray rack;
- Removable ventilated heating system for easy and convenient cleaning;
- $\circ~$  Temperature control via digital thermostat 30° 90° C;
- pair of push handles positioned on both short sides , with PVC handle supports, AISI 304-18/10 stainless steel grip tube, the handles can be used even with the doors open;
- $\circ \ \ \text{illuminated power switch with } \textbf{mains presence indicator} \ \text{light}; \\$
- $\bullet \ \ \textbf{temperature controlled} \ \ \textbf{by a digital thermostat-thermometer} \ , \ \textbf{a red light signals the functioning of the resistance};$
- $\circ\,$  removable ventilated heating system for easy and convenient cleaning;
- $\circ~$  internal supports with anti-tipping 'C' profiles, 77 mm pitch ;
- wheels with a diameter of 125 mm, two swivel with brake and two fixed with galvanized steel support;
- perimeter bumper in gray anti-track rubber.
- OPTIONAL ACCESSORIES:
- Door lock;
- Manual humidifier.

## MADE IN ITALY

## **TECHNICAL CARD**

power supply Monofase

Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	2
net weight (Kg)	135
gross weight (Kg)	145
breadth (mm)	812
depth (mm)	860
height (mm)	1995