Services and Technologies for professional catering since 1973

CODE	DESCRIPTION	PRICE/DELIVERY
TCF055-0100	GLASS WASHER-WASHING MACHINE Bar with SQUARE basket 350x350 mm, ELECTROMECHANICAL controls, 1 cycle of 120 sec, 30 baskets / hour, max glass height 250 mm, RINSE AID dispenser, V.230 / 1, Kw. 2.89, Weight 30 Kg, dim.mm.440x497x630h.	**Delivery** from 8 to 15 days

PROFESSIONAL DESCRIPTION

GLASS WASHER with SQUARE basket 350x350 mm or Round 350 mm diameter with Special Support, output 30 baskets / hour, ELECTROMECHANICAL controls :

- **wash and rinse arms** in **AISI 304 stainless steel** , easy to inspect;
- **completely molded self-cleaning tank** to facilitate the flow of impurities;
- **Thermostop system** to ensure rinsing at the right temperature for proper sanitization of the object to be washed;
- **anti-drip roof** ;
- **control panel** removable from the front;
- **ease of maintenance** : the most sensitive components have been positioned on the front of the machine (solenoid valve, thermostats, resistors, dispensers, pump, etc.);
- **predisposition drain pump** ;
- **standard rinse aid dispenser** ;
- **non-return valve as standard** ;
- single-walled bodywork;
- double-skinned door;
- **n. 1 wash cycle of 120 seconds** ;
- **hourly productivity: 30 baskets / hour** ;
- **useful washing height: 250 mm** ;
- water consumption per cycle 2 lt;
- tank capacity: 10 lt;
- boiler capacity: 3 lt;
- **washing pump power Kw.0,2** ;
- tank resistance: Kw.2,4;
- boiler resistance: Kw.2,7;
- dim.mm.440x497 / 788x630h.

NOTE:
- By ordering **the appropriate SUPPORT** , it is possible to use **round baskets with a diameter of 35 cm**

.
Supplied :
- 2 Glass Baskets 350 x 350 mm,
- 1 Spoon holder basket,
- 1 saucer rack,
- 1 Water Inlet Hose (length 2 meters),
- 1 drain hose (length 2.5 meters).

Accessories / Optional :
- **SUPPORT** for **round basket mod. 35x35 cm**
- ROUND basket diam. 35 cm,
- Detergent dispenser kit,
- Drain Pump Kit,

CE mark
Made in Italy

TECHNICAL CARD	
power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	2,89
net weight (Kg)	30
gross weight (Kg)	39
breadth (mm)	440
depth (mm)	497
height (mm)	630

TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY

TCF055-0170

Round Basket Support
Round basket support diam.35 cm

TCF055-0160

Square Basket 35x35
Square basket 35x35 cm

TCF055-0150

Round Basket
Round basket diam.35 cm

TCF055-0480

Detergent dosing kit
Detergent dosing kit

TCF055-0485

Drain Pump Kit
Underbase drain pump kit

	CAVO DI ALIMENTAZIONE
(EI)	POWER CORD SUPPLY
	CABLE D'ALIMENTATION
	CABLE DE ALIMENTACION

	CANNA DI CARICO G 3/4 L=2000 mm
(WI)	G 3/4 INLET HOSE L=2000 mm
	TUYAU D'ALIMENTATION G 3/4" L=2000 mm
	TUBO DE ALIMENTACION G 3/4" L=2000 mm

	TUBO DI SCARICO Ø 29 mm L=2500 mm
(D)	DRAIN HOSE Ø 29 mm L=2500 mm
	TUYAU DE VIDANGE Ø 29 mm L=2500 mm
	TUBO DE DESAGUE Ø 29 mm L=2500 mm

	TUBO DI SCARICO Ø 29 mm L=2500 mm (CON POMPA SCARICO)
(D-DP)	DRAIN HOSE Ø 29 mm L=2500 mm (WITH DRAIN PUMP)
	TUYAU DE VIDANGE Ø 29 mm L=2500 mm (AVEC POMPE DE VIDANGE)
	TUBO DE DESAGUE Ø 29 mm L=2500 mm (CON POMPA DE DESAGUE)