



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
BS-E9PQ4+FE	ELECTRIC COOKER 4 PLATES on ELECTRIC OVEN GN 2/1, BERTOS MAXIMA 900 line, HIGH POWER Series, with 4 SQUARE plates measuring 300x300 mm, INDEPENDENT CONTROLS, 6 power levels, V.400/3+N, Tot. Kw 21, 5, weight 138 kg, dim.mm.800x900x900h	

PROFESSIONAL DESCRIPTION

ELECTRIC COOKER with 4 SQUARE PLATES measuring 300x300 mm on ELECTRIC OVEN GN 2/1 (mm 530x650), MAXIMA 900 line, HIGH POWER series :

- **worktop in AISI 304 stainless steel**, front and **side panels in AISI 304 stainless steel**, Scotch Brite finish;
- one-piece watertight molded top;
- **cast iron square plates** with **surface 300 x 300 mm**, **3.5 kW each**, **reach 400°C** and are easily adjustable thanks to the **6-position selector which activates 6 different concentric power zones**;
- this **direct temperature control system** guarantees **significant energy savings** and makes these cookers ideal for maintenance cooking and for boiling large quantities of water;
- plates equipped with **safety thermostat**;
- **cooking zone power n° x Kw : 4 x 3.5**;
- **electric oven** with incoloy stainless steel heating elements with increased diameter;
- **grill with salamander function** in the upper part and **thermostat** that allows accurate **temperature regulation from 50 to 270 °C**;
- **oven power 7.5 kW**;
- **capacity 4 GN 2/1 trays** (530x650 mm);
- oven **chamber** in AISI 430, with 4-level supports and pressed and ribbed stainless steel inner door;
- **line indicator** and **temperature indicator**;
- Highly resistant handle in AISI 304 stainless steel, thickness 20/10.
- **3 year warranty**.

Accessories/Options :

- grill for GN 2/1 kitchen oven

CE mark

TECHNICAL CARD

power supply	Trifase
Volts	V 400/3 +N

frequency (Hz)	50
net weight (Kg)	138
breadth (mm)	800
depth (mm)	900
height (mm)	900



HIGH POWER

3,5 kW	3,5 kW	▶ 300x300 mm
3,5 kW	3,5 kW	



GN 2/1
530 x 650 mm x 4 pos.

