



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Trifase
Volts	V 400/3 +N
frequency (Hz)	50
net weight (Kg)	55
breadth (mm)	400
depth (mm)	900
height (mm)	900

PROFESSIONAL DESCRIPTION

ELECTRIC COOKER with 2 INDUCTION ZONES on OPEN CABINET, MAXIMA 900 Line, POWER INDUCTION Series :

- **worktop and front and side panels** in **AISI 304 stainless steel** ;
- stainless steel interior;
- **6 mm thick glass ceramic top** ;
- **perfectly smooth surface** which guarantees quick cleaning, in just a few gestures and in a few minutes, without the use of aggressive detergents;
- **maximum energy saving** as the heating of the cooking area is activated only when the pan is in direct contact with the surface;
- energy saving is ensured by the **immediate achievement of the maximum temperature** inside the cooking containers whilst keeping the hob completely cold;
- **the high energy efficiency is given by the absence of heat dispersion** and consumption reduced by over 30%;
- **the heating zone self-regulates** based on the diameter of the pan;
- **immediate automatic interruption when the pan is removed from the hob** ;
- **digital indicator** that immediately indicates the **set power level, from 1 to 9** ;
- power regulation via robust high-precision control;
- **square areas measuring 270 x 270 mm and power 5 kW** ;
- **cooking zone power n°x Kw : 2 x 5** ;
- **2 year warranty** .

Accessories/Options :

- right/left door per compartment

CE mark
Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
BS-E9P2M/IND	ELECTRIC COOKER WITH 2 INDUCTION ZONES on OPEN CABINET, BERTOS MAXIMA 900 line, POWER INDUCTION Series, with 2 SQUARE ZONES measuring 270x270 mm, INDEPENDENT CONTROLS, 9 power levels, V.400/3+N, Kw.10.00, Weight 55 Kg, dim.mm.400x900x900h	





MAXIMA 900



n.	2
mm	270 x 270
kW	5



380-415 V3N~ 50/60 Hz



TOT. kW	10
---------	----



Kg	55
----	----





POWER INDUCTION

5 kW	▶ 270x270 mm
5 kW	



900
35 3/8"

900
35 3/8"

400
15 3/4"

