



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>BS-E9F22-4MS-BF</b>	ELECTRIC FRYER on MOBILE, BERTO'S, MAXIMA 900 Line, TURBO Series, 1 TANK of 22 litres, BFLEX Electronic Controls, Enhanced version, V.400/3+N, Kw.22.00, Weight 55 Kg, dim.mm. 400x900x900h	<b>Delivery</b> from 15 to 25 days

#### PROFESSIONAL DESCRIPTION

**ELECTRIC FRYER on MOBILE, MAXIMA 900 Line, TURBO Series, 1 22 lt TANK , BFLEX ELECTRONIC CONTROLS, ENHANCED version:**

- **worktop and front and side panels in AISI 304 stainless steel ;**
- **Incoloy stainless steel heating elements** positioned directly inside the tank, which can be folded into a vertical position to facilitate cleaning operations;
- **safety device** for turning off the electricity supply with resistors in a vertical position;
- **temperature control via electronic control unit** with the following functions:
  - **temperature control from 100 to 190 °C ,**
  - **display of the set and working temperatures ,**
  - **" melting " and maintenance program at 100 °C** for the use of solid frying fats,
  - **self-diagnostics for any anomalies ;**
- **safety thermostat** with manual reset;
- **AISI 304 stainless steel tank** with large rounded edges and large cold area, below the heating elements, for settling residues;
- the top, with rounded edges, incorporates a slightly inclined surface for placing the baskets which facilitates the draining of the oil;
- **ball drain cock** , located inside the compartment, controlled by a handle with athermal grip, with steel collection tray;
- **24 month warranty .**

#### Supplied:

- single basket

#### CE mark

Made in Italy

#### TECHNICAL CARD

**power supply** | Trifase

<b>Volts</b>	V 400/3 +N
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	22,00
<b>net weight (Kg)</b>	55
<b>breadth (mm)</b>	400
<b>depth (mm)</b>	900
<b>height (mm)</b>	900



	<b>L</b>	22	
	<b>mm</b>	306 x 460 x 295 h	
	<b>mm</b>	260 x 400 x 150 h	
	<b>TOT kW</b>	18 (E9F22-4M-BF)	
	<b>kW</b>	22 (E9F22-4MS-BF)	
	<b>VOLT</b>	380-415 V3N~50/60 Hz	
	<b>Kg</b>	55	

