

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

REFRIGERATED CELLAR for WINE, Ventilated Refrigeration, capacity 260 Bordeaux bottles, Class A:

Customization

 the wine cellar fridge can be configured with multiple combinations of colors and frames by choosing the preferred combination between two colors for the structure (black and ivory) and four door frames (silver, black, light and dark).

Internal fittings

 Standard: Elegant black metal shelves that allow you to stack the bottles in order to reach maximum values in terms of capacity.

0

- $\bullet \ \, \text{The wine cellar can be customized with different internal layouts} \text{ , to be ordered separately (Optional)} : \\$
 - EXTRACTABLE DRAWERS: the drawers slide on guides that offer maximum fluidity and a cushioned end stop. Specific drawer
 holder brackets are necessary to guarantee this level of performance and reliability. The wooden front of the drawer is coordinated
 with the color of the external frame of the structure and has a seat designed for labeling the bottles.
 - SHELVES: elegant black metal shelves that allow you to stack the bottles in order to reach maximum values in terms of capacity.

Energy saving

- maximum reduction of dispersion from inside to outside and vice versa;
- o first wine cellar to adapt to the new EU legislation
- exceptional insulation with notable savings in operating consumption (60% savings compared to previous lines)

Maximum silence

 4 operating modes: Normal, Booster (up to -2° compared to the set setting), Silence (-4 db) and Economy (temperature conservation for up to 12 hours of stand-by out of service)

Ethical commitment

• Recycled and recyclable plastic materials are used for the body, and low-impact polyurethane foams for the insulating materials, made with CFC-free blowing agents. The refrigerant used is R290 (propane), a "naturally" green refrigerant gas.

<u>Design</u>

• New smart, young and modern design.

Conquest of space

Flexibility and functionality of the exhibition spaces

Tailored temperatures

• Always precise, constant and adjustable.

Ventilated refrigeration version

 \circ It allows you to maintain the chosen, uniform and constant temperature inside the refrigerated compartment .

Digital temperature control

 $\circ\,$ Temperature adjustable from +2° to +16°C

Door with double glazing and lock

- $\circ\,$ Double glazing made of double glass and large 14mm thick internal chamber .
- External glass and internal glass both TEMPERED.
- Internal glass made with the innovative magnetron system (very thin layer of metal oxide) to improve thermal insulation.
- Internal glass made with low emissivity (insulating treatment) to improve thermal insulation and to avoid the formation of humidity.
- $\circ~$ Thermal insulation of the internal glass with extremely low Ug thermal transmittance value.
- Channel on the chamber made with enhanced performance to facilitate thermal cutting.

Technical data:

- Capacity (in Bordeaux): 260 bottles (without internal accessories)
- Capacity 536 litres
- Energy Saving: Class A, only with glass door
- $\circ~$ Temperature: +2° (SET +2) / +16°C (SET +16)
- Interior LED lighting
- Gas Type R290: is a natural, highly efficient refrigerant fluid (up to 15% more efficient than R134a), designed for high performance and long life, has a ZERO Ozone Depletion Potential and a low GWP value (3 GWP).
- o Control Panel: Multi touch display
- Ventilated refrigeration
- Environmental Operating Conditions: TA 30°c 55% RH (Clim. Class 4)
- o Emission Level: 38 db (A)

Variants:

- 1. Structure color: Black, ivory
- 2. Frame Color: Black, silver, dark wood, light wood

Accessories/Options:

- Shelf (additional) complete with 4 spacers, max capacity 65 Bordeaux bottles
- Removable drawer

CE mark Made in Italy

TECHNICAL CARD

power supply	Monofase
--------------	----------

Volts V 230/1

frequency (Hz) 50

motor power capacity (Kw) 0,235

net weight (Kg) 135

gross weight (Kg) 150

breadth (mm) 820

depth (mm) 756

height (mm) 1962

135 Kg, dim.mm.820x756x1962h

AVAILABLE MODELS

EF-H2000/VNN



ENOFRIGO - Refrigerated Wine Cellar, Black Structure and Black Frame, Mod.H2000 / VNN REFRIGERATED WINE CELLAR, 1 glass door, black structure and black frame, capacity 260 bottles, temperature + 2 ° / + 16 ° C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight

Delivery from 8 to 15 days

EF-H2000/VNS



ENOFRIGO - Refrigerated Wine Cellar, Black Structure and Dark Wood Frame, Mod H2000 / VNS

REFRIGERATED WINE CELLAR, 1 glass door, black structure and dark wood frame, capacity 260 bottles, temperature + 2 $^{\circ}$ / + 16 $^{\circ}$ C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

EF-H2000/VNA



ENOFRIGO - Refrigerated Wine Cellar, Black Structure and Silver Frame, Mod.H2000 / VNA REFRIGERATED WINE CELLAR, 1 glass door, black structure and silver frame, capacity 260 bottles, temperature + 2 ° / + 16 ° C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

EF-H2000/VNC



ENOFRIGO - Refrigerated Wine Cellar, Black Structure and Black Frame, Mod H2000 / VNC REFRIGERATED WINE CELLAR, 1 glass door, black structure and light wood frame, capacity 260 bottles, temp. $+2\,^{\circ}$ / $+16\,^{\circ}$ C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235 , Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

Delivery from 8 to 15 days

EF-H2000/VAN



ENOFRIGO - Refrigerated Wine Cellar, Ivory

Structure and Black Frame, Mod H2000 / VAN
REFRIGERATED WINE CELLAR, 1 glass door, ivory
structure and black frame, capacity 260 bottles,
temperature + 2 ° / + 16 ° C, digital controls, ventilated
refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight
135 Kg, dim.mm.820x756x1962h



ENOFRIGO - Refrigerated Wine Cellar for Wine, Ivory Structure and Dark Wood Frame, Mod H2000 / VAS

REFRIGERATED WINE CELLAR, 1 glass door, ivory structure and dark wood frame, capacity 260 bottles, temp. $+ 2 \degree / + 16 \degree$ C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

EF-H2000/VAA



ENOFRIGO - Refrigerated Wine Cellar, Ivory Structure and Silver Frame, Mod H2000 / VAA REFRIGERATED WINE CELLAR, 1 glass door, vory structure and silver frame, capacity 260 bottles, temperature + 2°/+ 16°C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

EF-H2000/VAC



ENOFRIGO - Refrigerated Wine Cellar, Ivory Structure and Light Wood Frame, Mod.H2000 / VAC

REFRIGERATED WINE CELLAR, 1 glass door, ivory structure and light wood frame, capacity 260 bottles, temp. + 2 $^{\circ}$ / + 16 $^{\circ}$ C, digital controls, ventilated refrigeration, LED lighting, V.230 / 1, Kw.0,235, Weight 135 Kg, dim.mm.820x756x1962h

Delivery from 8 to 15 days

Delivery from 4 to 9 days

TECHNICAL CARD

CODE/PICTURES

DESCRIPTION

PRICE/DELIVERY



TECHNOCHEF - Shelf complete with 4 spacers, Mod.EF-RPN

Shelf complete with 4 spacers, max 65 bottles bordolesi capacity, dim.mm.691x515x35h

Dimensioni - Dimensions Mod. H2000 1962 820



































