



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TCF322-001500</b>	DISHWASHER square rack mm.500x500, front loading, ELECTRONIC controls, 4 cycles of 90/120/150/180 sec, max height of glasses 320 mm/plates 350 mm, with rinse aid and Tank detergent dispenser, V.400/3+N, Kw 5,9, Weight 69 Kg, dim.mm.585x610x815h	<b>Delivery</b> from 8 to 15 days

#### PROFESSIONAL DESCRIPTION

**DISHWASHER-GLASSWASHER with SQUARE RACK mm. 500x500, yield max n°40 baskets/hour, DIGITAL CONTROLS:**

- **Bodywork made entirely of AISI 304 steel ,**
- **Digital electronic** controls with display,
- **4 wash cycles of 90/120/150/180 seconds ,**
- **Max useful height: plates 350 mm ,**
- **Useful passage for glasses max 320 mm high ,**
- **Stainless steel LOWER and UPPER washing impeller** diameter 18 mm. with forged helical jets,
- **Stainless steel LOWER and UPPER rinse impellers** with **adjustable rotation speed ,**
- **Detergent dispenser Electric** washing programmable from the display,
- **Electric rinse aid dispenser** programmable from the display,
- Stainless steel washing detergent injector welded on the tank,
- Filter group in the tank for suction and discharge,
- Electrical **predisposition** for **drain pump ,**
- **Control system via electronic card with simple and extremely efficient Dip-Switch ,**
- **Setting and controlling the wash and rinse temperatures ,**
- Adjustable Thermostop function that guarantees better results,
- **Display showing temperatures and selected wash cycle ,**
- **Smart Start Button ,**
- **Self-diagnosis system ,**
- The electronic control allows you to manage various parameters to give you a great level of customization according to your needs while the self-diagnosis allows you to reduce machine downtime to a minimum by already suggesting some simple operations to perform to resolve the situation.
- **Notice of Scheduled Maintenance ,**
- Automatic additional rinse cycle,
- **1 Automatic drain cycle** (with drain pump installed),
- **Adjustable drain and rinse times ,**
- Temperature reading through precise NTC probes,
- **Wash and rinse impellers in stainless steel ,**
- **Double detergent and rinse aid dispenser installed as standard ,**
- **Tank capacity lt.24 ,**
- Tank resistance Kw.2,6,
- Boiler capacity lt.7,3,
- Boiler resistance Kw.5,4,
- Washing pump of Kw 0.52 (0.7 Hp),
- Recommended water hardness 7÷10 °f,
- Water consumption per cycle at 2 bar: 2.0 litres.

**Supplied:**

- 1 basket for glasses dim.mm.500x500x100h.
- 1 basket of 18 plates dim.mm.500x500x100.
- 2 cutlery containers.

**Accessories/Options:**

- **17516** - 0.5 Hp pressure pump installed
- **21116** - 32W installed drain pump.
- **23138** - 0.5 Hp pressure pump kit.
- **22440** - 32W drain pump.
- **18698** - Kit of 4 stainless steel adjustable feet 50-70 mm.
- **19584** - Open base support for dishwasher on adjustable feet, dim. mm. 580x565x450h + Feet H120-190 mm
- **23140** - Swing door for dishwasher base support Mod.SPI40
- **V230-3** - Optional 230V/3+T

**CE mark**  
**Made in Italy**

**TECHNICAL CARD**









<b>power supply</b>	Trifase
<b>Volts</b>	V 400/3 +N
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	5,92
<b>gross weight (Kg)</b>	69

breadth (mm) 585

depth (mm) 610

height (mm) 815

#### TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>TCF322-002605</b> 	<b>TECHNOCHEF - Kit 4 adjustable stainless steel feet</b> Kit 4 stainless steel adjustable feet 50-70 mm	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002604</b> 	<b>TECHNOCHEF - 32W drain pump kit</b> 32 W drain pump kit for glass-fronted and dishwasher front loading, post-sale installation	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002602</b> 	<b>TECHNOCHEF - Drain pump installed 32W</b> 32 W installed drain pump for glass-fronted and under-the-counter dishwashers	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002606</b> 	<b>TECHNOCHEF - Swing door for dishwashing base support</b> Swing door for dishwashing base support	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002603</b> 	<b>TECHNOCHEF - Pressure pump kit 0,5 Hp</b> 0.5 Hp rinsing pressure pump kit, after-sales installation, suitable for glass washers, undercounter dishwashers and canopy	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002601</b> 	<b>TECHNOCHEF - Pressure pump installed 0.5 HP</b> Rinsing pressure pump installed 0.5 Hp, suitable for glass washers, undercounter dishwashers and canopies	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002614</b> 	<b>TECHNOCHEF - Open base support with basket-holding guides</b> Open base support with basket guide rails for Undercounter dishwashers, dim.mm.583x524x566h	<b>Delivery</b> from 4 to 9 days
<b>TCF322-002607</b> 	<b>TECHNOCHEF - Basic dishwasher support</b> Base day support for dishwasher, dim.mm.580x565x450h + Feet H120-190 mm.	<b>Delivery</b> from 4 to 9 days

