

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



CODE	DESCRIPTION	PRICE/DELIVERY
TCF091-ARM030	Sanitizing cabinet with 1 door ozone generator, capacity 350 lt, V.230/1, Watt 65, dimensions 660×600×1450h mm	Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

NEUTRAL SANITIZING CABINET with OZONE GENERATOR . 1 Door . 350 lt :

- Cabinet for SANITIZING fruit, vegetables, kitchen utensils, work utensils, office objects, clothing, shoes, personal linen, bedroom linen, objects in general;
- · Operation with sensor, when the door is closed the sanitization cycle begins which must be confirmed by the user;
- o If confirmed, an orange LED lights up and remains for the entire duration of the cycle, including the Ozone degradation time;
- The green LED when lit indicates that the system is powered;
- The program is preset fixed in three phases :
 - Ozone creation phase (3 Min.);
 - Reaction phase Ozone (15 Min.);
 - Ozone decay phase (30 Min. *) (* The time may vary depending on: products, contamination, humidity, quantity)
- If the door is opened during sanitisation, the cycle stops immediately. The closure is hermetically guaranteed by a perimeter gasket;
- If it is used more than once a day, especially in narrow and unventilated environments, on request as an optional, the cabinet can be equipped
 with an extractor that allows the gases to escape to a centralized filtering system, otherwise opt for the installation of an internal recirculating
 catalyst system;
- The cabinet should never be opened until the cycle is finished.
- The SANITIZING cabinet also boasts the following features :
 - high-tech ozone generator,
 - $\circ~$ body entirely insulated in polyurethane thickness from 40 to 50 mm $\mbox{,}$
 - automatic door closing with magnetic seal to ensure that the internal compartment is airtight, a necessary condition for safety,
 - o possibility of removing odors and sanitizing;
- Product that could fall within the TAX CREDIT (DL 23/2020) defined at 50% of the sanitation costs up to a maximum of 20,000 euros (awaiting officialisation);
- The cabinets are not supplied with plugs;
- On request, possibility of external coloring White or Black Optional .

TECHNICAL DATA:

- o Capacity 350 litres
- o Grids n.3
- Power consumption 65 W
- o Dimensions mm (WxDxH) 660x600x1450h

Accessories/Options:

- o Activated carbon filter system for intensive use
- Activated carbon replacement filter, lasts 6 months
- o Stainless steel slotted surface mm. 470x490
- External white or black color surcharge

CE MARK MADE IN ITALY

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,065	
breadth (mm)	660	
depth (mm)	600	
height (mm)	1450	

