

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



CODE	DESCRIPTION	PRICE/DELIVERY
TCF091-FRG040	Sanitizing Refrigerator Cabinet with ozone generator 1 door, Professional, capacity 900 lt, temperature 0 ° / + 10 ° C, ventilated refrigeration, ECOLOGICAL Gas R290, V.230 / 1, Kw.0.38, Weight 90 Kg, dimensions mm 790x1010x2090h	Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

SANITIZING FRIDGE CABINET with OZONE GENERATOR, 1 Door, It. 900, Temp. 0 / + 10 ° C:

- Useful for long-term storage and sanitizing of all foods that would normally be kept fresh, with the advantage of lengthening their conservation;
- Equipped with a fully automated digital control device compliant with Industry 4.0 requirements;
- Timed control ozonator :
- The OZONE used in small quantities (1 min. Every 20 min.) Lengthens the shelf life of the products and keeps their quality intact;
- OZONE generator by electric generator with a maximum production of 250 MG / H (air powered) functioning by setting ON / OFF time:
- The wardrobe is equipped with :
 - Cooling element;
 - High technology ozone generator;
 - Forced ventilation , to ensure uniformity of the quality of Ozone inside the cell,
 - Digital instrument that controls the ozone temperature, times and the safety of any door opening.
- The system records all events and programs and is interconnected following the industry 4.0 criterion. To guarantee a good functioning of the system it is necessary to connect the device to the internet;
- Product included in the TAX CREDIT (DL 23/2020) Tax credit of 50% of the Sanitation costs up to a maximum of 20,000 euros (awaiting formalization).

TECHNICAL DATA

- Made of AISI 304 stainless steel;
- o Doors number 1;
- Suitable for containing 600x400 mm grids;
- · Racks with 62 mm pitch;
- Capacity 900 lt;
- \circ Operating temperature 0 ° / + 10 ° C;
- Insulation 75 mm;
- Ventilated refrigeration;
- Hot gas defrosting;
- ECOLOGICAL refrigerant gas R290;
- Climate class 5;
- Digital thermostat;
- $\circ \ \ \textbf{Standard ventilation stop} \ ;$
- $\circ~$ Ambient temperature of use from + 18 $^{\circ}$ to + 25 $^{\circ}$ C;
- Automatic closing door as standard;
- Standard lock;
- Internal lighting optional;
- Adjustable feet as standard;
- Single phase power supply;
- Power 380 W;
- Internal dimensions mm 640x850x1480h
- External dimensions mm 790x1010x2090h.

Included:

- $\circ\,$ n. 8 guides for grids
- on. 4 grids 600x400 mm

CE MARK MADE IN ITALY

MADE IN ITALI		
TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,38	
net weight (Kg)	90	
breadth (mm)	790	
depth (mm)	1010	
height (mm)	2090	