

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



	CODE	DESCRIPTION	PRICE/DELIVERY
	FC-G-S903-FC	Refrigerated saladette for salads with 3 DOORS, capacity 4 GN 1/1 containers (530x325 mm), Temp. + 2 $^{\circ}$ / + 8 $^{\circ}$ C, Static, ECOLOGICAL Gas R600a, V.230 / 1, Kw.0,235, Weight 104 Kg, dim.mm.1365x700x865h	Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION			

REFRIGERATED SALADETTE for SALADS with 3 DOORS, with WORKTOP prepared for 4 Gastro-Norm 1/1 CONTAINERS (530x325 mm):

- external structure in stainless steel;
- worktop in food-grade polyethylene;
- lid with telescopic opening;
- o capacity lt. 368;
- \circ temperature + 2 $^{\circ}$ / + 8 $^{\circ}$ C ;
- electronic thermostat;
- \circ 1 intermediate grid for GN1 / 1 door;
- $\circ\,$ static evaporator foamed on three sides with fan to uniform the temperature;
- Static refrigeration;
- ECOLOGICAL R600a refrigerant gas;
- automatic defrost at standstill;
- automatic evaporation of condensation water;
- o max ambient temperature / humidity: + 35 ° C / 50% HR;
- insulation thickness 35 mm.

Supplied:

- n ° 3 GN 1/1 grids (530x325 mm)
- $\circ\,$ n $^\circ$ 3 pair of guides.

Accessories / Optinals :

- GN 1/1 plasticized grid
- o pair of stainless steel guides

NB : Gastro-Norm basins EXCLUDED .

CE MARK Made in ASIA

Made in ASIA		
TECHNIC	TECHNICAL CARD	
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,235	
net weight (Kg)	104	
gross weight (Kg)	116	
breadth (mm)	1365	
depth (mm)	700	
height (mm)	865	
TECHNICAL CARR		

TECHNICAL CARD

CODE/PICTURES DESCRIPTION PRICE/DELIVERY

FC-GRP11-FC



Forcold - GN 1/1 plasticized grid

GN 1/1 plasticized grid (530x325 mm).

FC-CG11



Delivery from 4 to 9 days

Delivery from 4 to 9 days

Forcold - Pair of guides for grill Pair of guides for grille