

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TH-MATICMANU8	Semi-automatic cabinet purifier/softener, manual activation of regeneration via button, max flow rate 500 l/h, dim.mm.245x340x485h	<b>Delivery</b> from 8 to 15 days

## PROFESSIONAL DESCRIPTION

## SEMI-AUTOMATIC SOFTENER CABIN, with MANUAL ACTIVATION of REGENERATION THROUGH A BUTTON :

Max flow rate: 500 LT/H Min Pressure: 1.5 ATE Max pressure: 7 ATE

• Min - max water temperature : 2 - 35 °C

• Inlet - Outlet connection : 3/8 M

Drain Fitting: HOSE HOLDER DIAM.14 MM
Regeneration duration: 22' MINUTES

 $\circ~$  Quantity of salt consumed during Regeneration : 0.8~KG.

• Hardness Mixing System : Yes

Limestone is mainly responsible for all the problems of blockage and damage to pipes , taps , coils , boilers and a significant increase in energy consumption which is often not noticed. The advantages deriving from the use of softened water are concrete and tangible . The softener mod. MATIC MANU 8 has been designed to meet the needs of those who supply equipment for bars , large kitchens , restaurants , hotels and manufacturers or traders of coffee machines , roasters, ovens and dishwashers .

The main features of this softener are its **very small size**, its **compactness**, **suitable for installation in minimum spaces** and the **ease of carrying out the regeneration** which, combined with an application that can be downloaded on APPLE and ANDROID, allows the regeneration to be carried out correctly and within the times indicated, without waste of time.

## IDEAL FOR THE CONNECTION OF :

Ideal for convection ovens

Or:

N.1 Coffee machine 2 groups

**CE MARK** 

TECHNICAL CARD					
breadth (mm)	245				
depth (mm)	340				
height (mm)	485				