

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



CODE	DESCRIPTION	PRICE/DELIVERY
TD-FEDL10NEMIDV-NERONE	Electric CONVECTION OVEN for GASTRONOMY and PASTRY, capacity 10 Gastro-Norm 1/1 or mm.600x400 TRAYS (excluded), DIGITAL CONTROLS, 9 cooking programs, V.400/3+N, Kw.12.7, Weight 127 Kg , dim.mm.840x910x1150h	Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

ELECTRIC CONVECTION OVEN for GASTRONOMY and PASTRY, NERONE Line, version with DIGITAL CONTROLS:

- interior and exterior in stainless steel with external finishes in Scoth Bright;
- room with rounded corners;
- chamber size mm 680x480x840h;
- capacity 10 Gastro-Norm 1/1 or 600x400 mm trays (not included), 80 mm pitch;
- \circ double motor and double fan ;
- ventilation in the cooking chamber with reverse fans;
- $\circ~$ adjustable thermostat from 50° to 280° ;
- o digital control panel;
- electronic card with 9 cooking programs;
- $\circ~$ needle probe for core cooking and cooking at $\Delta~T^{\circ}$;
- door glass condensation recovery system with automatic evaporation;
- internal chamber and separate body to eliminate thermal expansion;
- semi-static cooking system with Italian refractory stone;
- electrical panel with extraction and quick maintenance;
- o door opening on the right (on the left on request);
- cold door with low-emissivity glass (openable internal glass);
- o open door rapid cooling system;
- door opening sensor;
- o cooking cycle repetition system;
- easy digitization for reading the cooking phases;
- interior lighting ;
- o interlocking door seal.

CE mark Made in Italy

TECHNICAL CARD Power supply Trifase Volts V 400/3 +N 50 12,7 150			
Volts V 400/3 +N frequency (Hz) 50 motor power capacity (Kw) 12,7 net weight (Kg) 127 gross weight (Kg) 150 breadth (mm) 840 depth (mm) 910	TECHNICAL CARD		
frequency (Hz) 50 motor power capacity (Kw) 12,7 net weight (Kg) 127 gross weight (Kg) 150 breadth (mm) 840 depth (mm) 910	power supply	Trifase	
motor power capacity (Kw) 12,7 net weight (Kg) 127 gross weight (Kg) 150 breadth (mm) 840 depth (mm) 910	Volts	V 400/3 +N	
net weight (Kg) 127 gross weight (Kg) 150 breadth (mm) 840 depth (mm) 910	frequency (Hz)	50	
gross weight (Kg) 150 breadth (mm) 840 depth (mm) 910	motor power capacity (Kw)	12,7	
breadth (mm) 840 depth (mm) 910	net weight (Kg)	127	
depth (mm) 910	gross weight (Kg)	150	
·	breadth (mm)	840	
height (mm) 1150	depth (mm)	910	
	height (mm)	1150	

TECHNICAL CARD

CODE/PICTURES DESCRIPTION PRICE/DELIVERY





GN 1/1 chromed grill

Gastro-Norm chromed grill 1/1 (mm 530x325)

TD-FOGRGPS



Delivery from 4 to 9 days

Delivery from 4 to 9 days

Chrome Pastry Grid

Chromed grill for pastry (mm 600x400)

TD-FOTGLPAS



Aluminum Pastry Tray Aluminum tray for pastry (mm 600x400)

Delivery from 4 to 9 days

TD-BIGN1/1-65



Delivery from 4 to 9 days

GN 1/1 stainless steel tray

Gastro-Norm 1/1 stainless steel tray (mm 530x325x65h)

TD-KITPIETRANEGN



Delivery from 4 to 9 days

GN 1/1 refractory stone plateGastro-Norm 1/1 refractory stone plate (mm 530x325x15)

TD-KITPIETRANEPS



Delivery from 4 to 9 days

Refractory stone plate

Refractory stone plate, dim.mm.600x400x15

TD-NEF0M



Technochef - BASE SUPPORT for NERONE MID OVENS

Support for NERONE MID ovens, with 10 pairs of guides for GN 1/1 and 600x400mm grids and trays, dim.mm 840x770x850h

Delivery from 4 to 9 days





