

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,215
net weight (Kg)	108
gross weight (Kg)	118
breadth (mm)	680
depth (mm)	710
height (mm)	2010

PROFESSIONAL DESCRIPTION

REFRIGERATED CABINET 1 door, capacity 429 litres, temp. -2°/+8°C, ECOLOGICAL in Class D, SNACK Line :

- $\circ \ \ \textbf{made} \ \text{of stainless steel} \ ;$
- external bottom and back panels in galvanized sheet metal;
- bottom with rounded corners;
- group incorporated in upper compartment;
- engine compartment with insulated sides;
- $\circ \ \ \text{capacity 429 litres} \ ;$
- operating temperature -2°/+8° C;
- electronic temperature control with digital thermostat;
- $\circ~$ refrigeration with fan and internal air conveyor to uniform the temperature ;
- pause defrost type;
- electric resistance around the door frame to eliminate condensation;
- elimination of condensation water using a basin;
- ECOLOGICAL refrigerant gas R600a;
- maximum ambient temperature: +35°C;
- maximum ambient humidity: 50% HR;
- o insulation thickness 60 mm;

- Door with return spring and reversible
- door lock with key;
- $\circ \ \ \text{door seal removable without tools;}$
- stainless steel feet , adjustable in height ;
- internal dimensions 560x580x1390h mm;
- external dimensions 680x710x2010h mm.

Supplied:

- o n.3 GN 2/1 grills
- o n.6 guides

Options/Accessories:

- Pair of grill guides
- Plasticized grill
- $\circ~$ Kit of 4 wheels, 2 of which with brake

CE MARK

CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-SNACK400TN-FC	1 Door Refrigerator Cabinet, Professional, Snack Line, 429 lt, temp2°/+8°C, with fan and internal air conveyor, ECOLOGICAL in Class D, Gas R600a, V.230/1, Kw. 0.215, weight 108 kg, dim.mm.680x710x2010h	Delivery from 8 to 15 days

CODE/PICTURES TECHNICAL CARD CODE/PICTURES DESCRIPTION FOR 4 to 9 days FC-GRPSN For cold - Plastic coated grid Pelivery from 4 to 9 days Pelivery from 4 to 9 days

