



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



**FORCOLD**

CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-G-GN600TN-FC</b>	1 Door Refrigerator Cabinet, Professional, lt.600, Temp.-2/+8°C, Static with fan and internal air conveyor, ECOLOGICAL in Class D, Gas R600a, Gastronorm 2/1, V.230/1, Kw.0,220, Weight 104 Kg, dim.mm.680x810x2010h	<b>Delivery</b> from 8 to 15 days
PROFESSIONAL DESCRIPTION		

**1-door REFRIGERATOR CABINET, capacity 600 litres, Temp. -2°/+8°C, ECOLOGICAL in Class D :**

- **Made of stainless steel ;**
- Bottom with rounded corners;
- External bottom and back panels in galvanized sheet metal;
- Group incorporated in upper compartment;
- Engine compartment with insulated sides;
- Capacity 600 litres;
- Suitable for containing **Gastronorm 2/1 grills** or containers (650x530 mm);
- **Electronic temperature control with digital thermostat ;**
- Operating temperature -2°/+8°C;
- **Static refrigeration with fan and internal air conveyor to uniform the temperature ;**
- Off-cycle defrost type;
- Electrical resistance around the door frame to eliminate condensation
- Elimination of condensation water using a basin;
- **ECOLOGICAL gas R600a ;**
- Maximum ambient temperature: +35°C;
- Maximum ambient humidity: 50% HR;
- **Insulation thickness 60 mm ;**
- Door with return spring and reversible;
- Door locking with key;
- Door seal removable without tools;
- Height-adjustable stainless steel feet;
- Internal dimensions 560x680x1390h mm;
- External dimensions 680x810x2010h mm.

**Supplied :**

- n.3 GN 2/1 grills
- n.3 pairs of guides



**Accessories/Options :**

- Pair of grill guides
- Plasticized grill
- Kit of 4 wheels, 2 of which have brakes

**CE MARK****TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,220
<b>net weight (Kg)</b>	104
<b>gross weight (Kg)</b>	118
<b>breadth (mm)</b>	680
<b>depth (mm)</b>	810
<b>height (mm)</b>	2010

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>FC-GRP21-FC</b> 	<b>Forcold - Plastic coated grid</b> Plastic coated grid	<b>Delivery</b> from 4 to 9 days
<b>FC-CG21</b> 	<b>Forcold - Pair of Guides</b> Pair of guides for grille	<b>Delivery</b> from 4 to 9 days

## FC-RU0120



Delivery from 4 to 9 days

### Forcold - 4 wheels kit, 2 with brake

4 wheels kit with 120 mm diameter, 2 of which with brake.

