

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



| FM-PV40LR23M  SINGLE, MEDIUM, Electric Glass-ceramic FryTop PLATE, Upper plate self-balanced RIGATA - lower plate SMOOTH; adjustable temperature from 0 ° to 300 ° C. V.230 / 1. | CODE         | DESCRIPTION   | PRICE/DELIVERY                   |
|--|--------------|---|----------------------------------|
| Kw 2, weight 17 Kg, dim. mm.490x450x190 / 600h   | FM-PV40LR23M | Upper plate self-balanced RIGATA - lower plate SMOOTH; adjustable temperature from 0 ° to 300 ° C, V.230 / 1, | <b>Delivery</b> from 4 to 9 days |

## PROFESSIONAL DESCRIPTION

## SINGLE, MEDIUM GLASS CERAMIC FRYTOP-PLATE, "Eurokera" type, with STRIPED SELF-BALANCED TOP and SMOOTH LOWER TOP:

- High resistance stainless steel external coating;
- Self-balanced ribbed top plate;
- **Smooth bottom** plate with a thickness of 5mm;
- Thermal insulation in **ceramic fiber**;
- Silicon glass electrical system with safety thermostat;
- Adjustable temperature from 0 ° to 300 ° C;
- Cooking surface dimensions: 400x300 mm;
- ${\color{gray} \bullet} \ \ \, \textbf{Cooking methods}: \textbf{contact and infrared cooking;} \\$
- It offers high resistance to thermal shocks, non-stick, non-porosity and therefore impermeability to flavors and odors;
- Ideal for cooking and reheating meat, fish, eggs, vegetables, cheeses, stuffed toast, sandwiches, etc;
- Quick and easy cleaning, thanks to the non-stick characteristics of the glass ceramic, allowing to eliminate the risk of bad smells due to food residues on the hobs;
- $\circ \ \ \textbf{Power light with LED lighting} \ ;$
- Maintaining the temperature with **minimum energy consumption**;
- Compact and elegant design;

## . CE MARK Made in Italy

| TECHNICAL CARD |          |  |  |
|----------------|----------|--|--|
| power supply   | Monofase |  |  |
| Volts          | V 230/1  |  |  |

| frequency (Hz)            | 5060 |
|---------------------------|------|
| motor power capacity (Kw) | 2    |
| net weight (Kg)           | 15,5 |
| gross weight (Kg)         | 17   |
| breadth (mm)              | 490  |
| depth (mm)                | 450  |
| height (mm)               | 190  |
|                           |      |