



PROFESSIONAL DESCRIPTION

REFRIGERATED PIZZA COUNTER 1 DOOR + 7-Drawer CHEST, with DEEP refrigerated SHOWCASE 330 0 380 mm, Temp.-2°/+8°C, ECOLOGICAL in Class C:

- **AISI 201 stainless steel structure ;**
- **Ventilated refrigeration ;**
- **operating temperature -2°/+8°C ;**
- Removable built-in unit for easy maintenance;
- Front panel that can be opened with a key;
- Gross capacity lt. 390
- **Circular pattern of the cold air** so as not to directly touch the product;
- **Electronic temperature control with digital thermostat ;**
- Electrical resistance around the door frame for the elimination of condensation;
- **Automatic defrosting** with electric heater and **automatic defrosting temperature control ;**
- Automatic evaporation of condensate water;
- Anti-corrosion treated evaporator;
- max temp. Operating / Ambient humidity °C/rh +35/50%;
- Door with return spring;
- **ECOLOGICAL GAS R600a;**
- **Energy CLASS C ;**
- insulation thickness: 60 mm;
- Door seal removable without tools;
- **Equipped with chest of drawers with 7 drawers (without cassettes)**
- **Complete with ingredient display cabinet 33 or 38 cm deep ;**
- Bottom with rounded corners;
- Feet in stainless steel AISI 201 stainless steel adjustable in height;
- Backrest in stainless steel;
- Possibility of leaning against the wall ;

CE mark
Made in ASIA

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
net weight (Kg)	346
breadth (mm)	1510
depth (mm)	800
height (mm)	1435

AVAILABLE MODELS

FC-G-PZ1610TN38-FC+VT



Delivery

Refrigerated Pizza Counter 1 DOOR + 7 DRAWERS, with 380 mm DEEP refrigerated display case

REFRIGERATED counter with 1 DOOR + 7 DRAWERS, refrigerated display case 380 mm deep, GN 1/3 container capacity (32.5x17.6 cm) + GN 1/2 (32.5x26.5 cm) temp. -2°/+8 °C, ECOLOGICAL CLASS C ventilated, GAS R600a, Kw.0,275, V.230/1, weight 346 Kg, dim.mm.1510x800x1435h

FC-G-PZ1610TN33-FC+VT



Delivery

Refrigerated Pizza Counter 1 DOOR + 7 DRAWERS, with REFRIGERATED SHOWCASE 330 mm deep

REFRIGERATED PIZZA counter 1 DOOR + 7 DRAWERS, refrigerated display case 330 mm deep, cap. basins n. 7 GN 1/4 (cm 26,5x16,2), temp.-2°/+8 °C, Ventilated ECOLOGICAL CLASS C, GAS R600a, Kw.0,275, V.230/1, weight 346 Kg, dim.mm .1510x800x1435h

