



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TCF133-SF-B500-95</b>	Professional countertop pastry sheeter with 950x500 mm BELTS-MATCHES equipped with UNDERPLATE for FLOUR and PASTRY COLLECTOR, mm ROLLING ROLLERS. 500 with opening from: 0 to 35 mm, weight 126 kg, 0.75 kW, dim. open mm. 2320x880x650h	<b>Delivery</b> from 4 to 9 days
PROFESSIONAL DESCRIPTION		

**Professional PASTRY SHEETER with 950x500 mm BELTS-MATS with under-top for collecting FLOUR and collecting sheets, roller opening from 0 to 35 mm, upward folding tables 950 mm long;**

- Designed and engineered to ensure **extremely easy and functional use** , in full compliance with international safety standards;
- **Reliable, solid and efficient structure**, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
- Shoulders and covers in cast aluminium;
- **Designed for extremely small spaces** ;
- Possibility of working **any type of pasta, up to very thin thicknesses**;
- **Micrometric adjustment** of the cylinder descent with aluminum handle;
- 
- Hard chrome **plated rolling cylinders** , ground and polished;
- **cylinder diameter: Ø6cm;**  
**cylinder opening: from 0 cm to 3.5 cm;**  
**cylinder width: 50cm;**
- 
- **Movement of the BELTS-MATCHES via joystick** ;
- 
- **Non-removable table** system;
- Tables equipped with **flour collection under-tops and dough catchers** at the bottom of the carpets;
- **1 speed of the BELTS:** (with differentiated speed between the entry belt and the exit belt);
- **Incoming belt speed: 16.50 m/minute; Output belt speed: 28.50 m/minute;**
- 
- **Stainless steel protection grills** with safety microswitch;
- **Tables that fold upwards** , so as to reduce the overall dimensions when the machine is at rest;
- **Working dimensions** : 2320 x 880 x 650h mm;
- **Dimensions at rest** : 690 x 880 x 1100h mm;
- 
- **Low voltage and dual control electrical system** (manual and pedal);
- **Accident prevention guards** , connected to the electrical system via limit switches;

**Optional:**

- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

**CE MARK**  
**Made in Italy**

**TECHNICAL CARD**

<b>power supply</b>	Trifase
<b>Volts</b>	V 400/3
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,75
<b>net weight (Kg)</b>	126
<b>breadth (mm)</b>	2320
<b>depth (mm)</b>	880
<b>height (mm)</b>	650