



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNOCHIEF.IT

CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-E500-71	Professional pastry sheeter with 710x500 mm BELTS-MATS equipped with UNDERPLATE for FLOUR and PASTRY COLLECTOR, REMOVABLE tables, 500 mm ROLLING rollers adjustable from 0 to 35 mm Weight 156 Kg, 0.75 kw, dim. open mm 1800x930x1100h	Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

Professional floor-standing PASTRY SHEETER, with 710x500 mm BELTS-MATS, with UNDERCOUNTER for FLOUR collection and PASTRY COLLECTION, Roller opening from: 0 to 35 mm, Foldable and EXTRACTABLE TABLES 710 mm long:

- Designed and engineered to ensure **extremely easy and functional use**, in full compliance with international safety standards;
- **Reliable, solid and efficient structure**, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
- Shoulders and covers in cast aluminium;
-
- **Possibility of working any type of pasta**, up to very thin thicknesses;
- Hard chrome plated **rolling cylinders , ground and polished ;**
- **Micrometric adjustment** of the cylinder opening with aluminum handle;
-
- **cylinder diameter: Ø 6 cm;**
- **cylinder opening: from 0 to 3.5 cm;**
- **cylinder length: 50 cm;**
- **Paste scraper on easily removable cylinders , for easy and effective cleaning;**
-
- **Movement of the BELTS-MATCHES via pedal control ;**
- **Variable speed conveyor belts-belts to avoid wrinkles in the pastry;**
- **Stainless steel protection grills** with safety microswitch;
- **Shielded bearings** to avoid flour infiltration;
- **Tables that fold upwards**, so as to reduce the overall dimensions when the machine is at rest;
- **Removable Table System with Stainless Steel Undertop for FLOUR Collection and Pasta Collector;**
- Mounted on wheels to facilitate movement;
- **Working dimensions** : 1800 x 930 x 1100h mm;
- **Dimensions when at rest** : 640 x 930 x 1470h mm;
-
- **Low voltage and dual control electrical system** (manual and pedal);
- **Accident prevention guards** , connected to the electrical system via limit switches;

Optional:

- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

CE MARK
Made in Italy

TECHNICAL CARD	
power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	0,75
net weight (Kg)	156
breadth (mm)	1800
depth (mm)	930
height (mm)	1100