

**TECNOSERVICE'21 srl** by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

OVEN for PIZZA Cuppone MICHELANGELO Line, 6 Pizzas x ø35 cm, Modular Modular, Available in 2 VERSIONS:							
•							
• Rounded stainless steel facade ;							
Cooking chamber in stainless steel dim. mm 1080x720x140; Cordierite brick hob; Evaporated rock wool insulation;							
							<ul> <li>Door with double panoramic glass and opening and closing system with compression spring;</li> </ul>
							Heat seal between door and cooking chamber;
<ul> <li>Integrated heat recovery system in the cooking chamber;</li> </ul>							
<ul> <li>Cooking chamber lighting with two 12V lamps;</li> </ul>							
<ul> <li>Safety thermostat and cooling fan;</li> </ul>							
<ul> <li>Armored and differentiated electric resistances on the ceiling and under the stalls;</li> </ul>							
<ul> <li>Electronically adjustable cooking steam vent;</li> </ul>							
• Separate command group ;							
o							
• Pizza capacity: 6 x diameter 35 cm							
• Rooms: 1							
• Power: 8.6 kW							
<ul> <li>Adjustable temperature from : 0-450 ° C</li> </ul>							
• Gross weight Kg: 20 8							
Cooking chamber dimensions 1080x720x1400h mm External dimensions 1550x1100x440h mm							
o							
o							
<ul> <li>All models can be supplied with a support (with or without wheels and, with the exception of the 435 model, with or without a cut for inserting the mixer) and with an extraction hood (with or without 5-speed motor).</li> </ul>							
VERSION WITH <b>DIGITAL CONTROLS</b> / Mod: <b>ML635L / 1CD</b>							
• Control system with <b>electronic card</b> ;							
<ul> <li>possibility to set the chamber temperature and the power of the resistance groups (top and floor) in different ways : "OFF" off, "MIN" 33% or "MAX" 100%;</li> </ul>							
• end of cooking buzzer;							
<ul> <li>programmable oven ignition with countdown up to 99 hours;</li> </ul>							

#### VERSION WITH TOUCH SCREEN CONTROLS / Mod: ML635L / 1TS

- Touch Screen control system with the possibility of setting the chamber temperature and the power of the two groups of resistances (top and floor) in a differentiated way from 0% to 100%;
- PYROLYSIS, ECONOMY and FAST RECOVERY functions integrated;
- cooking programming;
- end of cooking buzzer;
- weekly timer + agenda ;

### **Optional:**

- CP-KM635LNT Hood Without Motor;
- CP-KM635LAS Hood with Motor;
- $\circ~$  CP-SML635L / 1 Base support for 1 CAMERA;
- $\circ~$  CP-SML635L / 2 Base support for 2 ROOMS;
- CP-RS Wheels Kit for Base Support;
- **CP-PS** Cut on Lower Shelf Support for inserting mixers;

## Made in Italy CE MARK

TECHNIC	AL CARD
power supply	Monofase
Volts	V 400/3 +N
frequency (Hz)	5060

	otor power capacity (Kw)	8,6	
	net weight (Kg)	183	
	gross weight (Kg)	208	
	breadth (mm)	1550	
	depth (mm)	1100	
	height (mm)	440	
	AVAILABL	E MODELS	
CUP-ML635L/1CD			
	CUPPONE MICHELANGELO Electric Oven for 6 Pizzas, Ø 35 cm. Digital commands Electric Pizza OVEN, for 6 Pizzas, modular modular with chamber mm 1080x720x140h, Version with DIGITAL CONTROLS, MICHELANGELO Line, V. 380/3 + N, Kw 8,6, Weight 208 kg, dim. mm. 1550x1100x440h		Delivery from 4 to 9 days
CUP-ML635L/1TS	CUPPONE MICHELANGELO Electric Oven for 6 Pizzas, Ø 35 cm. Touch Screen Controls Electric Pizza OVEN, for 6 Pizzas, modular with chamber mm 1080x720X140h, Version with TOUCH SCREEN CONTROLS, MICHELANGELO Line, V. 380/3 + N, Kw 8,6, Weight 208 kg, dim. mm. 1550x1100x440h		<b>Delivery</b> from 4 to 9 days
	TECHNIC	AL CARD	
CODE/PICTURES		DESCRIPTION	PRICE/DELIVERY
CP-PS			<b>Delivery</b> from 4 to 9 days
		helf for inserting the mixers upport for Mixer Insertion	
CP-RS	<b>Wheels Kit for Bas</b> Modular 4 wheels kit professional pizza ov	with pedestal for Cuppone	<b>Delivery</b> from 4 to 9 days
CP-SML635L/1		ppone Michelangelo, for 1 Chamber, standard shelf, Optional Wheels,	<b>Delivery</b> from 4 to 9 days
CP-SML635L/2	Chambers, Steel Stru	<b>t for 2 Chambers</b> ppone Michelangelo, for 2 cture, Low standard shelf, Optional g, Dim. Mm. 1540x950x900h	<b>Delivery</b> from 4 to 9 days
CP-KML635LNT	Neutral Hood for Mich	<b>or for Michelangelo oven</b> nelangelo Oven, Stainless Steel, nt 70 kg, dim. mm. 1546x1200x410	<b>Delivery</b> from 4 to 9 days



**Hood with Motor for Michelangelo Oven** Extractor Hood for Michelangelo Oven, Stainless Steel, Adjustable Speed, Kw 0.13, 700 m3 / h, Weight 73 kg, dim. mm. 1546x1200x410





Delivery from 4 to 9 days





	320
H	
	000
	0
	CD

# VERSIONE CON COMANDI DIGITALI Mod: ML635L/1CD

- Sistema di controllo con scheda elettronica;

 possibilità di impostare la temperatura della camera e la potenza dei gruppi di resistenze (cielo e platea) in maniera differenziata: "OFF" spento, "MIN" 33% o "MAX" 100%;

- avvisatore acustico di fine cottura;

- accensione del forno programmabile con conto alla rovescia fino a 99 ore;





# VERSIONE CON TOUCH SCREEN Mod: ML635L/1TS

- sistema di controllo Touch Screen con possibilità di impostare la temperatura della camera e la potenza dei due gruppi di resistenze (cielo e platea) in maniera differenziata da 0% a 100%;
- funzioni PIROLISI, ECONOMY e RECUPERO VELOCE integrate;
- programmazione cotture;
- avvisatore acustico di fine cottura;
- timer settimanale + agenda;