

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



TCF18-STGALL700BLACKCF Cured Meat Storage and Seasoning Cabinet in Black Plastic-coated Steel, 1 Glass Door, max capacity 100 Kg, Temp. 0 ° / + 30 ° C, digital controls, V. 230/1, Kw.1,8, Weight Kg 176, dim. mm 750v850v 2080h	CODE	DESCRIPTION	PRICE/DELIVERY
Wegit Rg 170, dill. Hill. 730x030x 20001	TCF18-STGALL700BLACKCF	Plastic-coated Steel, 1 Glass Door, max capacity 100 Kg,	Delivery from 15 to 25 days

PROFESSIONAL DESCRIPTION

CURED MEAT STORAGE CABINET, 1 GLASS door, in Black Plastic-coated STEEL, Temp. 0 $^{\circ}$ / + 30 $^{\circ}$ C, max capacity 100 Kg, cm 75x85x208h, mod. STG ALL 700 BLACK CF:

Aging consists in giving a certain product a certain period of rest in suitable climatic conditions, in such a way that it quickly reaches an optimal result in terms of organoleptic qualities, aroma, fragrance and flavor, these are the stages of the process:

- **Stewing or dripping**: lasting a few hours, it favors the diffusion of aromas in the meat.
- **Drying**: lasting about 6 days; in this period there is a large loss of excess water from the product, which must be as uniform as possible, avoiding the hardening of the external casing.
- **Seasoning**: it has a variable duration based on the type of product; in this period a good humidity regulation helps the formation of natural enzymatic phenomena 'good molds' which favor the complete maturation of the product, so as to guarantee its conservation and healthiness.

The seasoning cabinet makes the most of your artisan product during the delicate seasoning process, by controlling humidity and ventilation, the system guarantees an ideal seasoning climate for up to 100 kg of cured meats in just 30 days.

FEATURES:

- internal lining in AISI 304 stainless steel;
- external coating in black plasticized steel;
- interior with rounded edges and printed bottom;
- o 75 mm insulation in ecological polyurethane;
- $\circ\,$ racks, grids and guides in AISI 304 stainless steel;
- $\circ~$ easily replaceable monobloc refrigeration unit;
- ventilated refrigeration with cataphoresis treated evaporator;
- $\circ~$ class N air condensing unit (max + 32 $^{\circ}$ C) ;;

0

• EVERtouch electronic control panel with 7 "touch screen display;

- functional features EVERtouch panel:
- ► 10 preset recipes
- ► 150 programmable recipes
- ► 20 distinct phases for each recipe
- constant display of internal temperature and humidity, of the remaining time of the phase in progress and of the icons with the function active;
- **USB port for import / export of** recipes, parameters, recorded data and any software update;
- o data log and HACCP alarms;
- o multilingual menu;
- quick setting and display of temperature, humidity, ventilation speed, air changes and running / parking ;
- o display of temperature, humidity, weight and Ph graphs;
- WiFi connection for total remote control management;
- internal lighting with K6500 LED bars (glass models);
- lock with keys;
- self-closing doors with 105 ° stop;
- o easily replaceable magnetic gaskets;
- height-adjustable stainless steel feet (130-200 mm);
- WiFi connection module for remote management;

0

- temperature adjustment range 0 / + 30 ° C;
- o active humidity regulation from 40% to 95%;
- **ECOLOGICAL GAS** refrigerant R452A (GWP 2141);
- o condensate collection with removable tray;
- $\circ\,$ requires connection to the water mains for humidity control and management .
- automatic defrost with electric resistance;

0

- Power supply: 230/1/50 Hz
- External dimensions mm. 750x850x2080h
- o Weight: Kg. 176
- Max capacity Kg. 100
- Meat / cheese version with capacity Kg. 150C / 100F

Included

- Cured meat version: 3 pairs of runners with 9 bars and 36 hooks
- Meat and cheese version: 5 pairs of guides with 5 plastic-coated grids

Accessories / Optionals :

- Scale for salami bar or meat hook
- o Salami carousel 2 rings
- o Ring for salami carousel
- o Pair of stainless steel guides for salami bars (40 Kg)
- o Pair of reinforced stainless steel guides for salami bars (55 Kg)
- o Stainless steel bar for salami hooks
- o Small stainless steel hook for salami mm 60 x 3
- o Pair of stainless steel guides
- o Stainless steel grid 65x53 cm
- Wheel application surcharge
- Stainless steel feet cover on 3 sides

CE MARK MADE IN ITALY

TECHNIC	AL CARD
power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	1,8
net weight (Kg)	176
gross weight (Kg)	188

	breadth (mm) 750	
	depth (mm) 850	
	height (mm) 2080	
	TECHNICAL CARD	
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
TCF18-PA2802	Small stainless steel hook for sala Small stainless steel hook for salami, di	
TCF18-PA1250	Stainless steel bar for salami hook Stainless steel bar for salami hooks	Delivery from 4 to 9 days
TCF18-PA1100	Pair of stainless steel guides for g Pair of stainless steel guides for grills	Delivery from 4 to 9 days
TCF18-PA1150	Stainless steel guides for salami b Pair of stainless steel guides for salami	Delivery from 4 to 9 days pars (40 Kg) i bars (40 Kg)
TCF18-PA0002	Stainless steel grid 65x53 cm Stainless steel grid, dim.mm.650x530	Delivery from 4 to 9 days
TCF18-PA1153	Reinforced stainless steel guides (55 Kg) Pair of reinforced stainless steel guides (55 Kg)	
Bank Karan		

TCF18-PA4000



Extra charge for wheel application

Extra charge for wheel application

Delivery from 4 to 9 days

Delivery from 4 to 9 days

TCF18- PA1803



Black foot cover on 3 sides

Black feet cover on 3 sides for mod. 700 ALL IN ONE MEAT / BLACK

TCF18-PA2810



Delivery from 4 to 9 days

Scale for salami bar or meat hook Scale for salami bar or meat hook



Delivery from 4 to 9 days

Salami carousel 2 rings Salami carousel 2 rings



