



CODE	DESCRIPTION	PRICE/DELIVERY
AK-513VSB	REFRIGERATED DISPLAY CASE for SUSHI, capacity 5 GN 1/3 trays, Class C, operating temperature 0°/+12°C, V.230/1, Kw.0,19, dim.mm. 1352x425x295h	Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

REFRIGERATED DISPLAY CASE for SUSHI, capacity 5 Gastro-Norm 1/3 TRAYS, Brand AMITEK :

- **plastic and glass structure ;**
- **capacity 5 Gastro-Norm trays 1/3 h 40 mm;**
- **temperature 0°/+12°C ;**
- Refrigeration in the lower part of the showcase only (GN tray compartment).
- **curved front glass ;**
- sliding glass doors;
- **digital thermostat ;**
- **static refrigeration ;**
- built-in refrigeration unit;
- **R600a refrigerant gas**
- **Energy CLASS C**
- automatic defrost display;
- digital switchboard;
- temperature humidity max **+33° C, 60 HR ;**
- also suitable for **Gastro-Norm containers 1/2 ;**
- **Sliding doors** on operator side.
- **Interior LED light** with ON/OFF switch.

Operating environmental conditions :

- Ambient Temperature Max 26°C.
- Relative Humidity 60 %

Note : Gastro-Norm 1/3 containers, h 40 mm, included.

CE mark

Made in China

TECHNICAL CARD

power supply | Monofase

Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,19
net weight (Kg)	39
gross weight (Kg)	50
breadth (mm)	1352
depth (mm)	425
height (mm)	295