



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

Mod.FM-FML6 - ELECTRIC PIZZA OVEN with 1 CHAMBER mm.720x1080x140h, with GLASS DOOR:

- **front cladding** in stainless steel ;
- **refractory hob** ;
- **thermal insulation** by rock wool coating;
- **1 chamber** of mm.720x1080x140h ;
- **2 adjustable thermostats** for **sole** and **top** ;
- chamber **temperature** from: **+50°** to **+500 °C** ;
- equipped with **pyrometers** ;
- **door with Pyrex inspection glass** ;
- ideal for cooking pizza, focaccia, etc.
- available in SINGLE- **PHASE** OR THREE- **PHASE** version.

CE mark

Made in Italy

TECHNICAL CARD

frequency (Hz)	50
motor power capacity (Kw)	9
net weight (Kg)	116
gross weight (Kg)	143
breadth (mm)	1010
depth (mm)	1210
height (mm)	420

AVAILABLE MODELS

FM-FML6/M**Technochef - Electric pizza oven, 1 chamber, mod. FML6**

ELECTRIC PIZZA OVEN with 1 CHAMBER
720x1080x140h mm, with GLASS DOOR, refractory hob,
2 ADJUSTABLE THERMOSTATS for BOTTOM and HEAD,
temp. From + 50 ° to +500 ° C, Weight 116 Kg, V.230 /
1 , kw 9, external dimensions mm.1010x1210x420h

Delivery from 8 to 15 days**FM-FML6/T****Technochef - Electric pizza oven, 1 chamber, mod. FML6**

ELECTRIC PIZZA OVEN with 1 CHAMBER
720x1080x140h mm, with GLASS DOOR, refractory hob,
2 ADJUSTABLE THERMOSTATS for BOTTOM and HEAD,
temp. From + 50 ° to +500 ° C, Weight 116 Kg, V.400 /
3 + N, kw 9, external dimensions mm.1010x1210x420h

Delivery from 8 to 15 days**TECHNICAL CARD****CODE/PICTURES****DESCRIPTION****PRICE/DELIVERY****FM-CAVFOFMD6****Technochef - SUPPORT STAND for FRESH PASTA MACHINE, MOD.ACCARMPF**

Support stand for mod. FMMPF1.5 - FMMPF2.5 - FMMPF4

Delivery from 8 to 15 days**FM-CAPPAFMD6****Technochef - SUPPORT STAND for FRESH PASTA MACHINE, MOD.ACCARMPF**

Support stand for mod. FMMPF1.5 - FMMPF2.5 - FMMPF4

Delivery from 8 to 15 days