

TECNOSERVICE'21 srl by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

Mod.FM-FML6+6 - ELECTRIC PIZZA OVEN for 6+6 Large Pizzas, 2 independent ROOMS of mm.720x1080x140h, MECHANICAL Controls:

• front cladding in stainless steel ;

- refractory hob ;
- thermal insulation by rock wool coating;
- 2 chambers of mm.720x1080x140h ;
- 4 adjustable thermostats for sole and top ;
- chamber **temperature** from: **+50**° to **+500** °C ;
- equipped with **pyrometers** ;
- $\circ~$ door with Pyrex inspection glass ;
- ideal for cooking pizza, focaccia, etc.
- available in SINGLE- **PHASE** OR THREE- **PHASE** version.

CE mark

Made in Italy

TECHNICAL CARD		
frequency (Hz)	50	
motor power capacity (Kw)	18	
net weight (Kg)	200	
gross weight (Kg)	231	
breadth (mm)	1010	
depth (mm)	1210	
height (mm)	750	
AVAILABLE MODELS		

FM-FML6+6/M	Technochef - Electric pizza oven, 2 chambers, mod. FML6 + 6 ELECTRIC PIZZA OVEN with 2 CHAMBERS of mm.720x1080x140h, with GLASS DOOR, refractory hob, 4 ADJUSTABLE THERMOSTATS for BOTTOM and HEAD, temp. From + 50 ° to +500 ° C, Weight 200 Kg, V.230 / 1, kw 18, external dimensions mm.1010x1210x750h	Delivery from 8 to 15 days	
FM-FML6+6/T	Technochef - Electric pizza oven, 2 chambers, mod. FML6 + 6 ELECTRIC PIZZA OVEN with 2 CHAMBERS of mm.720x1080x140h, with GLASS DOOR, refractory hob, 4 ADJUSTABLE THERMOSTATS for BOTTOM and HEAD, temp. From + 50 ° to +500 ° C, Weight 200 Kg, V.400 / 3 + N, kw 18, external dimensions mm.1010x1210x750h	Delivery from 8 to 15 days	
TECHNICAL CARD			
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY	
FM-CAVFOFMD6	Technochef - SUPPORT STAND for FRESH PASTA MACHINE, MOD.ACCARMPF Support stand for mod. FMMPF1.5 - FMMPF2.5 - FMMPF4	Delivery from 8 to 15 days	
FM-CAPPAFMD6	Technochef - SUPPORT STAND for FRESH PASTA MACHINE, MOD.ACCARMPF Support stand for mod. FMMPF1.5 - FMMPF2.5 - FMMPF4	Delivery from 8 to 15 days	