



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



Nota: Vedi nell'immagine aggiuntiva i colori disponibili

PROFESSIONAL DESCRIPTION

WINE CELLAR-TECA, Capacity 112 Inclined Bottles, STATIC or VENTILATED REFRIGERATION, suitable for WHITE or RED WINES:

- **aluminum structure,**
- Interior in Aluminum,
- Sliding Doors, Sides and Top **in GLASS,**
- **ECOLOGICAL** Refrigerant **Group** with GAS R 290a
- **digital thermoregulator** from : **+4°+16°C.**
- **automatic defrost,**
- **automatic evaporation of condensate,**
- **innovative refrigeration system based on the positioning of the cooling coil in the center of the showcase which guarantees better conservation conditions,**
- **SLIDING DOORS** in glass on **1 FRONT,**
- **door anti-fog system;**
- **natural white LED lighting on the posts,**
- **key lock ,**
- **Anti-vibration system,**
- **Ambient temperature: +25°, MAX for WHITE WINES**
- **Ambient Temperature: +30°, MAX for RED WINES**

4 POSSIBILITIES OF USE CONFIGURABLE by the Customer

- STATIC MULTITEMPERATURE from +6° to +16°C for WHITE and RED Wines,
- STATIC MULTITEMPERATURE from +14° to +20°C for RED Wines,
- VENTILATED for RED Wines with adjustable temperature from +14° to +16°C,
- VENTILATED for WHITE Wines with adjustable temperature from +6° to + 12°C;

Possible EQUIPMENTS, to be Selected at the TIME of the Order in the PRODUCT SHEET.

- **FRAME in MDF**
RAW, - MATT WHITE RAL-9010, - MATT BLACK RAL-9005, - GOLD VO1, SILVER VO2, - COLORS RAL 20 MATT LACQUERED, COLORS RAL 100 GLOSSY LACQUERED

DUNE FRAMES
RAW, - MATT WHITE RAL9010, - MATT BLACK RAL9005, - GOLD VO1 - SILVER VO2 - COLORS RAL20 MATT LACQUERED, COLORS RAL100 GLOSSY LACQUERED ;

OPTIONALS/ACCESSORIES:

- **Colored LED lighting** on the uprights with **remote control .**

CE mark

Made in Italy

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,45
net weight (Kg)	107
breadth (mm)	860
depth (mm)	530
height (mm)	1855

AVAILABLE MODELS

EO-TV-M12-RAL9005



CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with MATT BLACK WOODEN FRAME

WINE CASE with FRAME IN MATT BLACK WOOD, 3 GLASS SIDES, INCLINED cap.112 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-M01

CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with RAW MDF WOOD FRAME
WINE CASE with FRAME FRAME in RAW MDF WOOD, 3 GLASS SIDES, INCLINED cap.112 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-RAL9010

CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with MATT WHITE WOODEN FRAME
WINE CASE with FRAME FRAME in MATT WHITE WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DRAL9010

WINE CASE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE FRAME in MATT WHITE WOOD
WINE CASE with DUNE FRAME FRAME in WHITE WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DRAL9005

CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE FRAME in MATT BLACK WOOD
WINE CASE with DUNE FRAME FRAME in BLACK WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-V01

CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with GOLD painted WOODEN FRAME
WINE CABINET with WOODEN FRAME painted GOLD, 3 GLASS SIDES, INCLINED cap.112 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-V02

CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with SILVER painted WOODEN FRAME
WINE CABINET with SILVER painted WOODEN FRAME, 3 GLASS SIDES, INCLINED cap.112 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-RAL20

WINE CASE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with WOODEN FRAME in RAL20 colors
WINE CABINET with WOODEN FRAME in RAL20 colours, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-RAL100

WINE CASE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with WOODEN FRAME in RAL100 colors
WINE CABINET with WOODEN FRAME in RAL100 colours, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-D01**CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE FRAME in RAW WOOD**

WINE CABINET with DUNE FRAME FRAME in RAW WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DV02**CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE FRAME in SILVER painted WOOD**

WINE CABINET with DUNE FRAME in SILVER WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DV01**CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE FRAME in GOLD painted WOOD**

WINE CABINET with DUNE FRAME in GOLD painted WOOD, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DRAL20**CASE for WINE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE WOODEN FRAME in RAL20 colors**

WINE CABINET with DUNE FRAME FRAME in WOOD in RAL20 colours, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front ,V.230/1, Kw.0,45, Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

EO-TV-M12-DRAL100**WINE CASE, 112 Bottles, Doors on 1 Front, 3 Glass Sides, Version with DUNE WOODEN FRAME in RAL100 colors**


WINE CASE with DUNE FRAME FRAME in WOOD in RAL100 colours, 3 GLASS SIDES, cap.112 INCLINED bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front ,V.230/1, Kw.0,45,Weight 107 Kg, dim.mm.860x530x1855h

Delivery from 10 to 18 days

TECHNICAL CARD**CODE/PICTURES****DESCRIPTION****PRICE/DELIVERY****EO-OPT-RGB-A****Colored LED lighting with remote control**

Colored LED lighting with remote control, dim.mm.40x1600

Delivery from 4 to 9 days



TV-M12 / TE-M12

+



T1-M-*



T1-M-4

MDF non verniciato • Unfinished MDF • MDF non peinte Dune non verniciato • Dune unfinished • Dune non peinte



MDF 1
MDF non verniciato
unfinished MDF
MDF non peint



Dune 1
Dune non verniciato
Dune unfinished
Dune non peinte

Verniciatura a liquido • Liquid paint finish • Laquage par peinture liquide



RAL 9010
bianco opaco (20 gloss)
matte white (20 gloss)
blanc mat (20 gloss)



RAL 9005
nero opaco (20 gloss)
matte black (20 gloss)
noir mat (20 gloss)



VO1
verniciato oro
gold paint
peinture or



VO2
verniciato argento
silver paint
peinture argent



RAL
opaco 20 gloss - lucido 100 gloss
matte 20 gloss - glossy 100 gloss
mat 20 gloss - brillant 100 gloss

Verniciatura a liquido (Dune) • Liquid paint finish (Dune) • Laquage par peinture liquide (Dune)



RAL 9010
bianco opaco (20 gloss)
matte white (20 gloss)
blanc mat (20 gloss)



RAL 9005
nero opaco (20 gloss)
matte black (20 gloss)
noir mat (20 gloss)



VO1
verniciato oro
gold paint
peinture or



VO2
verniciato argento
silver paint
peinture argent



RAL
opaco 20 gloss - lucido 100 gloss
matte 20 gloss - glossy 100 gloss
mat 20 gloss - brillant 100 gloss

Rivestimento in foglia (Dune) • Leaf finish (Dune) • Revêtement en feuille métallique (Dune)




ORO1
oro patinato
gold coated
revêtement or



ORO2
argento patinato
silver coated
revêtement argent

POSSIBILI IMPOSTAZIONI • POSSIBLE SETTINGS • CHOIX DE RÉGLAGE




Le temperature riportate sono indicative e possono variare di ± 2 °C. L'utente può impostare la temperatura da +4 °C a +18 °C.
Reported temperatures are approximate and may vary by ± 2 °C. User-controlled temperature +4 °C to +18 °C.
Les températures indiquées sont approximatives et peuvent varier de ± 2 °C. L'utilisateur peut régler la température de +4 °C à +18 °C.

UNITÀ REFRIGERANTE INTEGRATA • SELF-CONTAINED REFRIGERATING UNIT • UNITÉ RÉFRIGÉRANTE INTÉGRÉE

IMPIANTO A REFRIGERAZIONE CENTRALE (brevettato) • CENTRAL COOLING SYSTEM (patented) • INSTALLATION DE RÉFRIGÉRATION CENTRALE (brevétée)




STANDARD



La serpentina di raffreddamento **1** e le ventole di aerazione interna **2** sono inserite al centro della vetrina all'interno dei pannelli di alluminio. Il compressore **3**, il condensatore orizzontale con ventola a pala premente **4** e la vasca per l'evaporazione della condensa **5** sono inseriti in una speciale vasca ribassata. Con questa soluzione, pur installando un compressore standard, l'altezza della base è limitata (150 mm) in quanto viene utilizzato lo spazio inferiore dove sono inseriti i piedi (40 mm). La circolazione dell'aria di condensazione avviene dalla parte inferiore frontale.







The cooling coil **1** and the internal fans **2** are installed in the middle of the cabinet inside the aluminium panels. The compressor **3**, the horizontal condensing unit, the pushing fan **4** and the vat for the evaporation of the condensation water **5** are placed in a special, lowered tank. With this solution, despite installing a standard compressor, the height of the base is limited (150 mm) as it takes up the lower space where feet are located (40 mm). Condensation air circulates from the bottom front part.

Le serpentin de refroidissement **1** et les ventilateurs internes **2** sont insérés au milieu de la vitrine à l'intérieur des panneaux d'aluminium. Le compresseur **3**, l'unité de condensation horizontale, le ventilateur avec la lame à pression **4** et le bassin de l'évaporation de l'eau de condensation **5** sont placés dans une cuve spéciale rabassée. Avec cette solution, même avec un compresseur standard, la hauteur de la base est limitée (150 mm), car on utilise l'espace inférieur où se trouvent les pieds (40 mm). La circulation de l'air de condensation est soufflé à travers la partie inférieure avant.

	circolazione aria interna • inside air flow • circulation de l'air interne
	aspirazione aria ambiente • cold air suction • aspiration de l'air ambiant
	espulsione aria calda • warm air outlet • expulsion de l'air chaud

IMPOSTAZIONE TERMOREGOLATORE • TEMPERATURE CONTROLLER SETTING • RÉGLAGE CONTRÔLEUR DE TEMPÉRATURE



-  Accende e spegne lo strumento • Turn on and off the appliance • Allume et éteint l'appareil
-  Accende e spegne la luce • Turn on and off the light • Allume et éteint l'éclairage
- SET** Per visualizzare/modificare Set point • View/change the set point • Pour afficher/changer le point de consigne
-  Per avviare sbrinatorio manuale • Start the manual defrost cycle • Pour lancer le dégivrage manuel
-  Per diminuire la temperatura • Decrease the temperature • Pour diminuer la température
-  Per aumentare la temperatura • Raise temperature • Pour augmenter la température
- RUX** Per attivare resistenza guide • Switch on rails heating • Pour activer le rechauffage du cadre des rails
-  Per attivare ventole interne • Switch on inside fans • Pour activer les ventilateurs intérieurs

