

**TECNOSERVICE'21 srl** by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



### BENCH VACUUM PACKAGING MACHINE, ECOVAC Line :

#### • made of stainless steel;

- vacuum chamber mm 360x400x190h, made of stainless steel pressed in one piece with rounded corners for maximum hygiene and ease of cleaning;
- 350 mm sealing bar , removable;
- fast welding cycle with adjustable time;
- digital control panel with 9 storable programs;
- 8/9.6 metres/cubic/hour vacuum pump ;
- transparent tank lid with automatic lifting by means of pistons;
- 1 program for marinating meat ;
- Sealing bar with completely removable wiring;
- Pump self-cleaning/heating system for optimal management of the packaging machine, with relative reduction of maintenance times and costs;
- $\circ~$  Cycle counter system for general appliance maintenance management;
- $\circ~$  GASTROVAC function for creating an external vacuum in GN containers;
- EXTRAVAC function, which offers a second vacuum phase lasting 5 seconds (particularly suitable for minced and boned meat);
- Fast Stop/Weld;
- Carter with 90° opening to facilitate access inside the packaging machine;
- Filling trays as standard;
- Adjustable hinges.

• Note : Possibility of external vacuum with the use of embossed envelopes (as visible in the photo).

#### **OPTIONALS/ACCESSORIES:**

• Possibility of vacuuming in external containers or gastro-norm trays using the special kit - Code EMATUBOGN.

- Arrangement for inert gas kit Code EMGASINERTE.
- Sealing Bar with Piston Lifting Cod. EMBSP.
- Sealing bar with bag surplus cut (scrap ) Code EMTS.
- Bell stop bar Cod.EMBF.
- Inclined plane for liquid packaging Cod.EMPI.
- Trolley for machine support Cod.EMCR.

## CE mark

# Made in Italy

TECHNICAL CARD	
power supply	Monofase
Volts	V 230/1
frequency (Hz)	5060
net weight (Kg)	42
breadth (mm)	460
depth (mm)	530
height (mm)	420











