



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TCF091-000301	1 Door Refrigerator Cabinet, Professional, external structure in stainless steel, 700 lt, Temp.-2°/+8°C, ECOLOGICAL in Class C, Gas R290, ventilated, V.230/1, Kw.0.24, Weight 80 Kg, dim.mm.720x800x2020h	<b>Delivery</b> from 8 to 15 days

#### PROFESSIONAL DESCRIPTION

##### 1-door FRIDGE CABINET, capacity 700 litres, temperature -2°/+8°C, ECOLOGICAL in Class C :

- **monocoque with 60 mm insulation** with HFO polyurethane foam, which has a GWP level 0;
- **the material used is stainless steel with a prevalence of Aisi 304** , excluding non-visible parts;
- Monoblock type units use **R290 gas** (GWP equal to 3) which **leads to significant energy savings** ;
- **defrosting with hot gas** , and not with resistance, allows for energy savings and defrosting is carried out more quickly;
- **partially channeled ventilation** to have correct air circulation inside the cell;
- **the guides have a hand-saving fold** , removable racks;
- **the fan stop microswitch when the door opens is mechanical** and does not need to be moved if the opening direction is changed;
- **the door is reversible** , simply fit the lower hinge on the side opposite to;
- the internal set-up is interlocking and is easily removable to ensure maximum convenience in cleaning operations;
- the delivery mouth, in ventilated cabinets, is protected by a channel, which guarantees that the cold outgoing air is not hindered by products or ice formations;

##### TECHNICAL DATA :





- Capacity (lt): 700
- Energy class: C
- Operating temperature: -2°/+8°
- Electrical power (Kw): 0.24
- V\Hz: 230/50
- Refrigerant gas: R290
- Weight (Kg): 80
- Dimensions (cm): 720x800x2020

**CE MARK**  
**MADE IN ITALY**

### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,24
<b>net weight (Kg)</b>	80
<b>breadth (mm)</b>	720
<b>depth (mm)</b>	800
<b>height (mm)</b>	2020

### TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>TCF091-000308</b> 	<b>Pair of stainless steel guides</b> Pair of stainless steel guides for GN 2/1 grills (mm 650x530)	<b>Delivery</b> from 4 to 9 days
<b>TCF091-000306</b> 	<b>GN 2/1 plasticized grill</b> Gastro-Norm 2/1 plasticized grill (650x530 mm)	<b>Delivery</b> from 4 to 9 days
<b>TCF091-000307</b> 	<b>Stainless steel grill GN 2/1</b> Gastro-Norm 2/1 stainless steel grill (650x530 mm)	<b>Delivery</b> from 4 to 9 days
<b>TCF091-000309</b> 	<b>Stainless steel wheels</b> Stainless steel wheel kit, diameter 125	<b>Delivery</b> from 4 to 9 days

