



CODE	DESCRIPTION	PRICE/DELIVERY
CZRS60	Refrigerated counter display case for 6 gastro-norm 1/3 basins, double temperature above / below: + 2 / + 6 ° C °, V.230 / 1, Kw.0,105, Weight 45 Kg, dim.mm.1438x395x245h	Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

REFRIGERATED EXHIBITION SHOWCASE by Banco, capacity 6 Gastro-norm containers 1/3, h 40 :

- **Ideal for the display** of **Panini, Tartine, Sushi** and everything else that needs to be kept in a refrigerated environment;
- **static refrigeration** ;
- compressor stop defrost;
- digital thermostat;
- **operating temperature from + 2 ° C to + 6 ° C** ;
- sealed compressor with sub-tropicalized ventilated condenser;
- **double temperature up / down for foods with maximum cold demand** ;
- insulation in CFC-free polyurethane with a thickness of 25 mm and a density of 40 kg / m³;
- **low consumption LED tape lighting system** ;
- external decoration with anodized aluminum profile;
- **molded tray in stainless steel, suitable for GN1 / 3 trays with 60 mm height** ;
- **curved hinged tempered glass for easy cleaning** ;
- high resistance sliding doors;
- trays included;
- capacity lt.45;
- R600a refrigerant;
- noise level dB (A) 55.

Environmental operating conditions:

- Ambient temperature Max 26 ° C.
- Relative humidity 60%

CE marking
Made in ASIA

TECHNICAL CARD

power supply Monofase

Volts V 230/1

frequency (Hz) 50

motor power capacity (Kw) 0,105

net weight (Kg) 45

breadth (mm) 1438

depth (mm) 395

height (mm) 245