

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



| CODE | DESCRIPTION | PRICE/DELIVERY |
|--------------------------|---|-----------------------------------|
| FC-M-GN1410TNG-FC | Professional refrigerated cabinet, 2 glass doors, with monobloc, plug-in system, ventilated, 650 lt, Temp.+0°/+8°C, GN 2/1, Ecological in Class C, Gas R290, V.230/ 1, Kw.0,508, Weight 206 Kg, dim.mm.1480x830x2010h | Delivery from 8 to 15 days |
| PROFESSIONAL DESCRIPTION | | |

REFRIGERATED CABINET 2 GLASS DOORS , Professional Line, It.1300, Ventilated, GN 2/1, Temp.+0°/+8°C, with Monobloc, Plug-in system, Class C: • made of AISI 201 stainless steel; • ventilated refrigeration; • Monobloc refrigeration unit; o refrigeration unit with plug-in system characterized by easy and immediate installation or possible removal/replacement; o silent motor; monobloc protected by stainless steel sheet; • temperature +0°/+8°C; $\circ\,$ electronic temperature control with digital thermostat ; • energy class C; • ecological refrigerant gas R290; • maximum ambient temperature: +32°C; o maximum ambient humidity: 60%HR; • electric resistance around the door frame to eliminate condensation; • insulation thickness 60 mm; • automatic defrost; $\circ\,$ electronic control of the defrost temperature ; automatic evaporation of condensation water; • anti-corrosion treated evaporator; o door with return spring and reversible; · door lock with key; o door seal removable without tools; internal LED light; bottom with rounded corners; external bottom and back panels in galvanized sheet metal; • Height-adjustable feet.

Supplied:

- o 6 GN 2/1 grills
- o 6 pairs of guides

CE MARK

| TECHNICAL CARD | | |
|---------------------------|----------|--|
| power supply | Monofase | |
| Volts | V 230/1 | |
| frequency (Hz) | 50 | |
| motor power capacity (Kw) | 0,508 | |
| net weight (Kg) | 206 | |
| gross weight (Kg) | 227 | |
| breadth (mm) | 1480 | |
| depth (mm) | 830 | |
| height (mm) | 2010 | |
| | | |

