

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
MC-3370GS	REFRIGERATED READY-TABLE PLATE TROLLEY in the version with 15 GRILLS of mm.650x650 for a total of 60 PLATES with MAXIMUM DIAMETER of 310 mm. o 90 PLATES with MAXIMUM DIAMETER of 200 mm, temp. working temperature between + 6 / + 10 $^{\circ}$ C, V.230, Kw.0,7, dim.mm.830x770x1900h	<b>Delivery</b> from 4 to 9 days

## PROFESSIONAL DESCRIPTION

REFRIGERATED READY-TABLE PLATE TROLLEY in the version with 15 GRILLS of mm.650x650 for a total of 60 PLATES with MAXIMUM DIAMETER of 310 mm. o 90 PLATES with MAXIMUM DIAMETER of 200 mm:

- external and internal structure entirely in stainless steel sheet;
- **insulation** with high density polyurethane foam injection;
- $\circ$  operating temperature between: + 6 ° and + 10 ° C;
- Static refrigeration;
- tempered glass doors that open up to 180 °, with rounded edges and PVC gaskets in the ledge, which can be removed for easier cleaning;
- hinges with snap closure;
- $\circ~$  side push handles in stainless steel tube with PVC supports;
- inside equipped with 15 adjustable grids in mm.650x650 plasticized wire able to accommodate 90 plates with a diameter up to 200 mm or 60 plates with a diameter up to 310 mm;
- control panel with digital thermostat-thermometer and ignition switch;
- **bumpers** in the 4 corners positioned in the lower part;
- spiral power cord, 3 meters long;
- swivel wheels with 12.5 cm diameter, 2 of which with brakes.

## **Environmental operating conditions:**

- o Ambient temperature Max 26 ° C
- Relative humidity 60%

## CE marking Made in Italy

MC-A0055		<b>Chilled refrigerated carts</b> Plastic grid mm.650x650 per cart Mod.MC3370G  Delivery from 4 to 9 days		
CODE/PICTURES		DESCRIPTION	PRICE/DELIVERY	
TECHNICAL CARD				
	height (mm)	1900		
depth (mm)		770		
	breadth (mm) 830			
motor power capacity (Kw)		0,7		
	frequency (Hz)	5060		
Volts		V 230/1		
	power supply	Monofase		