



| CODE             | DESCRIPTION   | PRICE/DELIVERY                    |
|------------------|---|-----------------------------------|
| <b>TP-KB82-R</b> | DISPLAY HOT DISPLAY counter, with 2 PLANS, STAINLESS STEEL STRUCTURE, glass on 4 sides, Plexiglas drop-side doors operator side, complete with HUMIDIFIER, temperature from + 30 ° to + 90 ° C, suitable for GN 1/1 + 1 pans / 2, V.230 / 1, Kw.1.00, dim.mm.870X370X390h | <b>Delivery</b> from 8 to 15 days |

#### PROFESSIONAL DESCRIPTION

#### DISPLAY HOT EXHIBITOR bench top, 2-STOVE IN STAINLESS STEEL, suitable for GASTRO-NORM 1/1 + 1/2:

- **furnishing object** able to **enhance the exposed product and the environment** in which it is installed;
- **structure in stainless steel sheet**, with scotch brite brushed finish;
- **glass on all 4 sides** for displaying baked pastry products, croissants, muffins, etc.;
- **2 stainless steel shelves**;
- the **useful space** in height **for the shelves is 15 cm**;
- plexiglass **drop doors on the operator's side**;
- **heating** obtained with a **high efficiency radiant resistance** housed in a special container, controlled by a **thermostat adjustable from + 30 ° to + 90 ° C** and an indicator lamp;
- a water drawer in stainless steel allows **the humidification of the products**;
- base frame is supplied with a removable tray, suitable for housing **Gastro-Norm 1/1 + 1/2 bowls**;
- uprights with rounded square section and, together with the upper frame, give the structure an **exceptional sturdiness**;
- **sides and front** are in 4 mm thick **tempered glass**;
- the **upper surface** is in 5 mm thick **tempered glass**, fixed to the structure with 4 sturdy wide-head screws;
- the hinges applied with a pressure screw allow the **almost total opening of the door** (170 °);
- on-off light switch, plug-in cable with plug;
- adjustable feet for perfect leveling.

#### ACCESSORIES / OPTIONAL:

- On request fall doors on the 2 fronts (self-service use).
- On request intermediate glass shelves.

**CEMade brand in Italy**

#### TECHNICAL CARD

|                                  |          |
|----------------------------------|----------|
| <b>power supply</b>              | Monofase |
| <b>Volts</b>                     | V 230/1  |
| <b>frequency (Hz)</b>            | 50       |
| <b>motor power capacity (Kw)</b> | 1        |
| <b>net weight (Kg)</b>           | 24       |

|                     |     |
|---------------------|-----|
| <b>breadth (mm)</b> | 870 |
| <b>depth (mm)</b>   | 370 |
| <b>height (mm)</b>  | 390 |