



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
breadth (mm)	750
depth (mm)	740
height (mm)	1300

PROFESSIONAL DESCRIPTION

BLAST CHILLER-FREEZER with UNIVERSAL GUIDES for 7 GASTRO-NORM 1/1 GRIDS/TRAYS (mm.530x325) or mm. 600x400, TECNODOM brand:

- **internal and external structure** made of **stainless steel** with rounded internal corners;
- **internal dimensions** : mm.760x630x410h;
- **capacity** : **7 Gastro-Norm 1/1 trays (mm.530x325) or mm.600x400** ;
- **CFC-free polyurethane insulation** , injected at high pressure;
- chamber dimensions mm 610x410x760;
- **insulation thickness : 60 mm** ;
- removable top;
- **door with self-closing** and **magnetic seal** ;
- front panel with **electronic control board with chamber probe** and **core probe** ;
- **ventilated refrigeration with air agitator** ;
- **easily removable and tropicalized refrigeration unit as standard** (ambient temperature +43°C and relative humidity of 65%) operating with R404A/R507 gas;
- **yield: POSITIVE CYCLE +90°+3° / Kg.25, NEGATIVE CYCLE +90°-18° / Kg.15;**
- **opening rear compartment** and **removable unit** , for easy maintenance;
- **evaporator defrosting by time**, at the end of the cycle, and lower tray for containing condensation water;
- height-adjustable stainless steel feet (60/90 H mm) .

Included:

- Chamber probe, core probe and n. 14 universal steel guides.

Accessories/Optional :

- universal steel guides - Cod.TD-GUABB.
- Gastro-Norm 1/1 plasticized grid (mm.530x325) - Cod.TD-GRPLTGN.
- kit 2 wheels with brake and 2 wheels without brake - Cod-TD-RUOABB.

CE MARK**MADE IN ITALY****AVAILABLE MODELS****TD-ATT07**

TECNODOM - BLAST CHILLER for 7 GN 1/1 TRAYS or mm. 600x400, output POSITIVE CYCLE +90° +3°C / Kg.25, NEGATIVE CYCLE +90°-18° / Kg.15, V. 230/1, Kw.1.49, dim.mm.750x740x1300h

Delivery from 8 to 15 days