



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
EM-MAXI	PROFESSIONAL BELL VACUUM PACKAGING MACHINE EUROMATIC on CABINET with WHEELS, CHAMBER mm.920x570x220h, 2 SEALING BARS of 500 and 900 mm, VACUUM PUMP of 100/120 meters / cubic / hour, V.380 / 3, Kw.2,4, Weight 200 Kg, dim.mm.1040x680x1050h	Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

BELL VACUUM PACKAGING MACHINE on CABINET with WHEELS, with 2 SEALING BARS of 500 and 900 mm :

- **made of stainless steel ;**
- **vacuum chamber 920x570x220h mm** , made of stainless steel molded in a single piece with rounded corners for maximum hygiene and easy cleaning;
- **2 sealing bars of 500 and 900 mm, removable ;**
- **vacuum pump of 100/120 meters / cubic / hour ;**
- **19 editable and customizable programs;**
- **1 program for marinating meat;**
- double sensor "empty + liquids";
- **piston sealing bar** , completely devoid of wiring for optimal and safe management of tank cleaning;
- **self-cleaning / heating system of the pump** for optimal management of the packaging machine, with relative reduction of maintenance times and costs;
- **STEPVAC function** for creating the vacuum of liquid products inside traditional vacuum bags;
- **GASTROVAC function** for creating external vacuum in GN containers;
- **EXTRAVAC function** , which offers a second vacuum phase lasting 5 seconds (particularly suitable for minced and boned meat);
- reinforced sealing function for sealing thick bags and / or bags containing liquid / wet products;
- quick stop / weld;
- carter with 90 ° opening to facilitate access to the inside of the packaging machine;
- standard filling platforms;
- adjustable hinges;
- empty cycle at choice: by time or by percentage with automatic start at closing of the bell and automatic reopening at the end of the cycle;
- transparent tank lid with automatic lifting;
- possibility of extra vacuum up to 99.9% for very humid products;
- **Step Vac** for emulsifiable products (vacuum cycle in stages).


ACCESSORIES / OPTIONALS:

- possibility of vacuuming in external containers or Gastro-Norm basins by means of a special kit - Code EMATUBOGN.
- predisposition for inert gas kit - Code EMGASINERTE.
- label printer - Code EMST.
- vacuum sensor in the chamber - Code EMSV.
- sealing bar with piston lifting - Code EMBSP.
- sealing bar with envelope excess cut (scrap) - Code EMTS.
- additional sealing bar - Code EMBS.
- bell stop bar - Code EMBF.
- inclined plane for liquid packaging - Code EMPI.

CE mark**Made in Italy****TECHNICAL CARD**

power supply	Trifase
frequency (Hz)	50/60
motor power capacity (Kw)	2,4
net weight (Kg)	200
breadth (mm)	1040
depth (mm)	680
height (mm)	1050

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
EM-BF 	TECHNOCHEF - Bell holder, Mod.BF Bell stop bar	Delivery from 4 to 9 days

EM-PI



Inclined plane, Mod.PI

Inclined surface for liquid packaging, suitable for bell-shaped packaging machines

Delivery from 4 to 9 days

EM-TUBOBN



Tube with adapter sleeve in gastro containers

Tube with adapter sleeve in gastro containers

Delivery

EM-GASINERTEURANO



TECHNOCHEF - Inert gas, Mod. GASINERTE

Inert gas kit for vacuum chamber machines

Delivery from 4 to 9 days


EM-ST



TECHNOCHEF - Label printer, ST mod

Label printer for bell packaging machines

Delivery from 4 to 9 days






STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA


STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello multifunzione digit - 10 PRG
Multifunction digit panel - 10 PRG



Sistema autopulizia olio
Oil made auto cleaning system



Pannello comandi a totale tenuta
contro umidità
Waterproof control Panel



Soft vacuum elettronico
Electronic soft vacuum



Vasca inox con angoli stondati
senza saldature
Entirely printed stainless steel
vacuum chamber, with internal
round corners



Connessione per attacco gastrovac
Connection for the gastrovac system




Set tavole di riempimento in
polietilene
Polyethylene filling squares set



DISPOSIZIONE BARRE SALDANTI

SEALING BARS POSITION

MAXI



STANDARD OPTIONAL

OPTIONAL PER CONFEZIONATRICI A CAMPANA
OPTIONALS ONLY FOR CHAMBER MACHINES



Installazione gas inerte
Arrangement for idle gas



Installazione stampante
Printer installation



Pompa Bosch
Bosch Pump



Saldatura con pistoni senza cavi
Sealing with cableless pistons



Barra saldante aggiuntiva
Extra Sealing Bar



Taglio Eccedenza
Exceeding cutting bar



Sensore di vuoto
Vacuum sensor



Sistema bloccaggio campana
Lid Hook



Altezza camera maggiorata
Increased chamber height



Piano inclinato per liquidi
Inclined plane for liquids



Tensione e frequenza speciale
Voltage and special frequency